

Supplementary files belonging to the *lineno.sty* distribution

Lazy ASCII → PDF listings

Uwe Lück

February 16, 2011

Preface

`lineno.sty` is a macro package made by Stephan I. Böttcher for attaching line numbers to L^AT_EX documents. Some people have used it for revising submissions in collaboration with referees or co-authors. Documentations are nowadays preferred to be in Adobe's PDF—so `lineno.sty`'s documentation is `lineno.pdf`¹.

`ednotes.sty` uses `lineno.sty` for critical editions, combining it with Alexander I. Rozhenko's `manyfoot.sty`—this was Christian Tapp's idea, who then hired me for adding the T_EXnical details. In doing this, I had to change some internals of `lineno.sty`, so Stephan transferred maintenance to me; then some of my macro files that I originally had made for `ednotes.sty` wandered into the `lineno` directory of CTAN—because they turned out not to need `ednotes.sty`, just to work as extensions of `lineno.sty`.

Now, I haven't had the time for making `.dtx` versions of the `.sty` files for `ednotes`. Therefore, ordinary `.pdf` documentation for the remaining `.sty` files of `lineno` is missing. What you see here is nothing but a somewhat structured listing of the additional `.txt` and `.sty` files in PDF, deriving from the `verbatim` package and its `\verbatiminput` command. I hope the high quality (scalable) output is worth it.

By contrast, the new package `fnlineno.sty` added in 2011 for footnote line numbers is documented in `fnlineno.pdf`² in high quality, using the `nicetext`³ bundle.

U. L.

¹<http://mirror.ctan.org/macros/latex/contrib/lineno/lineno.pdf>

²<http://mirror.ctan.org/macros/latex/contrib/lineno/fnlineno.pdf>

³<http://mirror.ctan.org/macros/latex/contrib/nicetext>

Contents

1	The .txt files	2
1.1	Summary: README.txt	2
1.2	Licenses/Copyright: COPYING.txt	6
1.3	Update summaries: CHANGEs.txt	7
1.4	Source file infos: SRCFILEs.txt	11
2	Tabular and array environments	11
2.1	edtable.sty	11
2.2	ltabptch.sty	24
3	\linelabel and notes from <i>math</i> mode: edmath0.sty	30
4	Extended line number references: vplref.sty	35

1 The .txt files

1.1 Summary: README.txt

README

```
lineno.sty v4.41
fnlineno.sty v0.55
```

2011-02-16

The LaTeX package `lineno.sty` provides line numbers on paragraphs. After TeX has broken a paragraph into lines there will be line numbers attached to them, with the possibility to make references through the LaTeX `\ref`, `\pageref` cross reference mechanism.

```
% Copyright 1995--2003 Stephan I. Boettcher <boettcher@physik.uni-kiel.de>;
% Copyright 2002--2005 Uwe Lueck, http://www.contact-ednotes.sty.de.vu,
%                               for versions 4.x and code from former Ednotes
% Copyright 2011      Uwe Lueck as above, for fnlineno.sty/tex/pdf
%                               bundle--author-maintained.
%
```

```
% The files listed below can be redistributed and/or modified under
% the terms of the LaTeX Project Public License; either
% version 1.3a of the License, or any later version.
```

```
% The latest version of this license is in
%   http://www.latex-project.org/lppl.txt
```

```
% We did our best to help you, but there is NO WARRANTY.
```

```
** [ UL: A few festive words on history and responsibility **
**       are next preceding hard facts as to (see lower) **
```

```

**      o 'Files' and                **
**      o 'Installation and usage'.  ] **

```

2004-09-13 Uwe L"uck [(UL)] is new maintainer for lineno.sty.

lineno.sty served the purpose for which I wrote it years ago. Uwe L"uck uses lineno.sty with his Ednotes package, which required quite a few changes and fixes. His package depends on lineno, therefore Uwe agreed to take over the maintenance of lineno.sty.

lineno.sty v4.0 includes most of the well tested changes that Uwe needs for Ednotes. These changes blend well into the concepts of the package, so I am happy to let it go.

From here on it is Uwe's, and he may proceed to mangle it as he likes. Expect some radical changes. You may find him to be quite a bit friendlier towards the poor souls who still use Windows :-). Currently, you need some kind of Unix environment to extract the source documentation from the sty file.

If some version 3 users run into difficulties with Uwe's newer versions, but need a minor bug-fix in version 3, please do not hesitate to ask me for help. But all requests for new features or major changes shall go to Uwe.

Cheers
Stephan

```

[ Thanks! And please let me know as well should
compatibility problems arise! The announced radical
changes are postponed again this time (v4.1).
--Ednotes is in
  http://mirror.ctan.org/macros/latex/contrib/ednotes.
                                           Uwe ]

```

Changes: see CHANGES.txt; earlier:

```

2004-10-19 UL: package options for tabular and math
2004-09-03 UL: merge Ednotes changes, taking over lineno.sty

2002 .. 2003 FMi, UL, SiB: bug fixes
2001-08-04 SiB: linenomath wrapping for \[ \]
2001-07-30 SiB: [hyperref] option obsolete.
2001-01-17 SiB: LaTeX class option [twocolumn] support

```

2001-01-04 SiB: LaTeX class option [fleqn] support
 2000-12-18 SiB: longtable compatibility
 2000-07-01 SiB: extra \newlabel items, [hyperref] option
 2000-03-10 SiB: indirect call of \output, to work with multicol.
 1999-08-28 SiB: fixed the footnote problem using \holdinginserts
 1999-06-11 SiB: included the extensions into lineno.sty
 1999-03-02 SiB: Added LPPL License

Files (cf. SRCFILES.txt):

README.txt	This file.	(v4.1: UL)
CHANGEs.txt	Differences to previous versions.	(v4.1: UL)
COPYING.txt	The LPPL header.	
SRFILES.txt	Source file infos	(UL 2011)
lineno.sty	The package itself, ready to use.	
edtable.sty	Module for tabular environments.	(UL, v4.1)
edmath0.sty	Module for \linelabel in math mode.	(UL, v4.1)
flineno.sty	Add-on for footnote line numbers	(UL, v0.55)
lineno.tex	The source for the documentation (generated)	
lineno.pdf	PDF deriving from the former.	(v4.1: UL)
lnosuppl.pdf	PDF listing of present non-PDF files	
ulinen.tex	The pathetic attempt of a users' manual. [Describes v3.1 currently.]	(UL, v4.1)
ulinen.pdf	PDF of former.	
vplref.sty	Conditionally include page number in line number references	(UL, v4.2)

As of version v3.00, the extension packages for lineno have all been incorporated into lineno.sty itself. Except for itemrule.sty, which was removed.

Home:

<http://mirror.ctan.org/macros/latex/contrib/lineno/>

TDS version:

<http://mirror.ctan.org/install/macros/latex/contrib/lineno.tds.zip>

Authors:

Uwe L"uck <http://contact-ednotes.sty@web.de>
 Stephan I. B"ottcher <boettcher@physik.uni-kiel.de>

Compatibility with other packages:

wrapfig.sty works since v2.05

multicol.sty works partly since 3.02.
Do NOT use \linelabel. Do NOT put a multicol in
internal vertical mode {table}, {figure}, etc.

hyperref.sty \ref to a \linelabel works since v3.03.

longtable.sty broke with lineno.sty loaded, but not enabled.
This is fixed in v3.04.

amsmath.sty loadable, but not fully supported, with v4.41

Installation and usage (UL, v4.1):

For being able to use ALL the new lineno.sty options, the following files must be "visible" to (La)TeX ("visible" explained below for beginners):

lineno.sty, edtable.sty, ednmath0.sty, ltabptch.sty

as above ("Home", note that clicking on "entire directory" suffices);

longtable.sty -- from the standard LaTeX Tools bundle.

Usage always starts with loading lineno.sty by \usepackage. The remaining .sty files are loaded automatically on the lineno.sty options (and we recommend not to load them through [the mandatory argument of] \usepackage).

For details, see lineno.tex/pdf and the .sty files mentioned above--search especially for tabular and math mode. (+ 'print' below here).

"Visible to (LaTeX)": Some users don't understand this "visibility" for a while, and indeed it may be somewhat non-trivial. These users may find help in

<http://mirror.ctan.org/macros/latex/ednotes/visible.txt> .

E.g., former users of lineno.sty may just put all the .sty files into the folder (at their workplace) where they had placed lineno.sty before. (UL, /v4.1)

To print the documented source:

Take the style-file 'lineno.sty', and feed it to a Un*x shell.
(Or download the extracted source documentation 'lineno.tex'.)

```
csh> source ./lineno.sty
sh> . ./lineno.sty
```

[I.e., type 'sh lineno.sty' (e.g.) as a UNIX command line.
Problems with awk may arise. I therefore switched to nawk
in lineno.sty v4.00, but this may trouble you as well. (UL)]

(Please ignore the error message at the beginning about the iffalse.)

Please have a look at a similar work of Michal Jaegermann and James
Fortune:

<http://mirror.ctan.org/obsolete/macros/latex/contrib/numline/>

=====
<- End of official README.txt (UL)

Changes Feb. 2011: numline obsolete, mirror.ctan.org, fnlineno,
amsmath compatibility, CHANGES.txt, lineno.tds.zip
Changes for v4.1 (Oct. 2004): minor fixes (removed 'supported/', e.g.);
bracketed text; lines with '(UL)'; redistribution with README only.
Formerly:

lineno.sty v4.0

\$Id: README,v 3.6.2.1 2004/09/13 20:15:47 stephan Exp \$

CTAN:macros/latex/contrib/supported/lineno
CTAN:macros/latex/contrib/supported/numline/

1.2 Licenses/Copyright: COPYING.txt

```
% lineno.sty
%
% The files in this directory are
```

```

%
% Copyright 1995--2003 Stephan I. B"ottcher <boettcher@physik.uni-kiel.de>;
% Copyright 2002--2005 Uwe L"uck, http://contact-ednotes.sty.de.vu,
%                               for versions 4.x and code from former Ednotes
%                               bundle--author-maintained.
% Copyright 2011                Uwe L"uck, http://contact-ednotes.sty.de.vu,
%                               for fnlineno.sty/tex/pdf
%
% The files can be redistributed and/or modified under
% the terms of the LaTeX Project Public License; either
% version 1.3a of the License, or any later version.
% The latest version of this license is in
%   http://www.latex-project.org/lppl.txt
% We did our best to help you, but there is NO WARRANTY.
%
% =====
<- (UL) End of official declaration.

```

History:

```

add. fnlineno          2011/02/16 ul
This file -> The files 2004/10/12 ul
$Id: COPYING,v 3.0.2.1 2004/09/13 20:15:47 stephan Exp $
LPPL v1.3a 2004/10/26

```

1.3 Update summaries: CHANGES.txt

CHANGES for lineno bundle 2011/02/16:

1. new fnlineno.sty for numbering footnote lines + \linelabel,
described in fnlineno.pdf

2. new overview SRCFILES.txt

CHANGES for lineno.sty v4.41 2005/11/02:

1. Loadable after amsmath.

2. Removed some nonsense from documentation.

CHANGES for lineno.sty v4.4 2005/10/27

[failed to be uploaded to CTAN, but distributed by mail]:

1. Proper effective line depth at end of paragraphs.
The spacing bug was quite obvious in two-column mode when a paragraph end was at a column bottom.
2. Another bug concerning two-column mode that had been introduced in v4.22 has been removed again.
3. Support for `\addvspace` introduced more and more bugs in versions of v4.32 and v4.33. The reasons seem to be clear now, and v4.4 should be stable.

CHANGES for `lineno.sty` v4.32 2005/10/17:

1. Support for `\addvspace`
(a math display or a list meets a heading -- or a sub-heading follows a heading -- or the like)
2. Clearly explained former option 'displaymath' and its change to a default.

CHANGES for `lineno.sty` v4.31 2005/10/01:

1. `\modulolinenumbers*` and a package option 'modulo*' for printing first line number after interrupting editor's text, regardless of the modulo.
2. Improved explanation of `\firstlinenumber` and package options.

CHANGES for `lineno.sty` v4.3 2005/05/16:

1. Option 'displaymath' (proper numbering at paragraphs containing math displays) becomes default.
2. Compatibility with `hyperref` now indeed (at least much more).
3. Tidied up documentation: terrible confusion of `\newcounter` vs. `\stepcounter`; sections on the same matter written at different times; ...
4. Additional internal improvements that perhaps hardly are observable (no more spurious linenumbers in math displays from vertical mode; some compatibility with packages that use

`\holdinginserts; \linelabel` in headings etc.).

CHANGES for `lineno.sty` v4.22 2005/05/09:

1. Restored "global" version of numbering lines of a `\parbox` or `minipage` or ... (I had missed and disabled this in taking over `lineno.sty`), explained in documentation (`lineno.pdf/dvi` subsec. 7.2).
2. Enabled `\flushbottom` in two-column pagewise or switching mode.
3. Re-implemented modulo mode -- disabling certain users' tricks see `lineno.pdf` sec. 5.5, also for a still supported substituting trick.
4. Tidied up setting the next line number globally vs. locally (`TeXbook` p. 301).
5. Tidied up discussions (in documentation) of possible changes in implementation.

CHANGES for `lineno.sty` v4.21 2005/04/28:

Removed serious flaws with math display, + something ...

CHANGES for `lineno.sty` v4.2 2005/04/26:

1. Re-enabled package option 'displaymath' (needed rearrangement after sec. 5).
2. New package option 'addpageno' for adding page numbers to line number references -- see sec. 6.1 of `lineno.pdf`.
3. Improved support for `\includeonly` (and improved sec. 5.3, p. 27).
4. Improved compatibility with other packages that change `\output` (`tameflts.sty`, e.g., for saving footnotes against `\marginpar` and floats), added advice on this matter -- sec. 2.3, pp. 7, 14f.

CHANGES for lineno.sty v4.11 2005/03/08:

1. The ‘edtable’ option now supports math environments like ‘array’. This requires updating edtable.sty to v1.3. (The claim in previous versions of edtable on this support simply was wrong, sorry.) For how to make use of this support, we urge you to read the usage instructions in edtable.sty (v1.3). These have been extended very much, structured more clearly, and supplied with examples.

2. `\linelabel` now complains when appearing outside line numbering mode. This counters Stephan Boettcher’s original intention, but I generalize from my own experience that it is helpful to be told when you have forgotten to switch into line numbering mode and (e.g.) wonder why all the line number references are 1 ... ednotes.sty users profit as well (at least I expect and hope that anybody profits, which, to be sure, does not mean that I hope that anybody forgets to switch ...).

3. The subsection on ‘edtable’ in lineno.sty/tex/pdf was not quite correct or complete -- corrected, improved.

4. The final list of user commands in lineno.sty/tex/pdf has not been complete. This has not changed, but it is briefly explained what is missing and where it can be found.

CHANGE 2005/01/20:

We have devised macros for indexing with line numbers, yet we don’t take the time to release them officially. If you are interested, please ask via

<http://contact-ednotes.sty.de.vu>

CHANGES for lineno.sty v4.1 2004/10/19:

Extension packages from the Ednotes bundle for enabling `\linelabel` in math mode and tabular environments are now handled through new package options ‘mathrefs’, ‘edtable’, ‘longtable’, and ‘nolongtablepatch’. Two of these extension packages moved from the ednotes folder to the lineno folder. lineno.tex/pdf has been updated accordingly.

CHANGES for `lineno.sty` v4.00 2004/09/03:

- o incorporated earlier extension packages `linenox0.sty`, `linenox1.sty`, `lnopatch.sty` (which belonged to the Ednotes bundle before);
- o adopted LaTeX Project Public License v1.3.

1.4 Source file infos: SRCFILES.txt

```
*File List*
edtable.sty      2005/10/03 v1.3c arrays with lineno + ednotes (ul)
edmath0.sty     2005/01/10 v0.2b math support for lineno/ednotes (ul)
fnlineno.sty    2011/01/07 v0.55 numbers to footnote lines (UL)
  lineno.sty    2005/11/02 line numbers on paragraphs v4.41
  vplref.sty    2005/04/25 v0.2a page-line cross-refs
fnlineno.tex    2011/02/14 documenting fnlineno.sty (UL)
lnosuppl.tex    2011/02/16 documenting supplementary files
ulineno.tex     2001/08/03 lineno.sty users manual
*****
```

```
List made at 2011/02/16, 12:41
from script file srcfiles.tex
```

2 Tabular and array environments

`lineno.sty`'s package options `edtable`, `longtable`, and `nolongtablepatch` redefine L^AT_EX tabular and array environments such that `lineno` and `ednotes` commands can be used inside. The code for these options resides in separate files at present. We are listing them here.

2.1 `edtable.sty`

```
%% 'edtable.sty'---Uwe L"uck, direction Christian Tapp.
%% LaTeX package for tables with line numbers and
%% editorial notes.
%%
%% Copyright (C) 2003-2005 Uwe L"uck--author-maintained.
%%
\def\fileversion{1.3c} \def\filedate{2005/10/03}
%%
%% This file can be redistributed and/or modified under
```

```

%% the terms of the LaTeX Project Public License; either
%% version 1.3 of the License, or any later version.
%% The latest version of this license is in
%% http://www.latex-project.org/lppl.txt
%% We did our best to help you, but there is NO WARRANTY.
%%
%% Please send your comments via
%%
%% http://www.contact-ednotes.sty.de.vu
%%
%% * USAGE: *
%
% *Requirements/overview:*
%
% The package is made for the background of the LaTeX2e macro
% package and enhances functionality of the following packages:
% 1.) Stephan I. B"ottcher's 'lineno.sty' for printing line
%    numbers in the margin and a \label version \linelabel
%    relating labels to line numbers;
% 2.) our 'ednotes.sty' for indicating variant readings and
%    other editorial remarks in separate footnote apparatuses;
% 3.) David Carlisle's 'longtable.sty' for multi-page tables.
%                                     %% TODO: supertabular etc.!?
% 4.) our 'ltabptch.sty' for a patch of 'longtable.sty'
%    (i.e., optionally, see below).
%
% Actually, only the first package is necessary for using the
% present one. The present one needs your line numbering commands
% according to the first one and its documentation to which we
% refer here. We likewise refer to the remaining packages for the
% details of their functionality.
%
% 'lineno.sty' version 4.1 and (in case it is used) 'ednotes.sty'
% version 0.8 (onwards) are needed. For obtaining recent versions
% of required packages, see the CTAN folder
%   /macros/latex/contrib/ednotes.
%
% *Install/load:*
% 1.) To be used, the present file must be put into a folder
%    that (La)TeX searches. You should have obtained a file
%    containing more detailed hints about this.
% 2.) We recommend loading this file *not* by
%    \usepackage[<options>]{edtable} but by loading 'lineno.sty'
%    or 'ednotes.sty' with package option 'edtable'.
% 3.) To use the package options 'longtable' and
%    'nolongtablepatch' that are described below, enter them

```

```

%      as options for 'lineno.sty' or 'ednotes.sty'.
%
% *User Commands:*
%
% 1. The package defines an environment 'edtable' -- for its
% syntax we consider two cases:
% (a) Let <stdtable> be a tabular environment "like 'tabular'".
% "Like" here means: (i) we have tested it with 'tabular', but
% it should work with many more (e.g., from the 'array' and
% 'tabularx' packages) -- which share certain properties of
% implementation and requirements. Sorry, you must try, or we
% hope you will (and tell us). (For wizards: <stdtable> may
% probably be anything using a single \halign and \tabskip=Opt.)
% Definitively:
% (ii) LaTeX's standard 'array' and other environments are not
% "like" 'tabular'. Namely, environments that work only in math
% mode are not meant here. They are considered below in 'b.'.
% (iii) 'longtable' from the 'longtable' package of the 'tools'
% bundle neither is meant. An option of the present package
% deals with it as described below. Neither 'supertabular' is
% meant.
% (iv) In general, usage with tabular environments that can
% break across pages as in (iii) is not recommended, at least
% when working with 'ednotes.sty'. Even if some worked here, a
% shortcoming with 'ednotes.sty' would be that the footnotes can
% appear on bad pages.
% -- Now the syntax is:
%   \begin{edtable}{<stdtable>}<args><entries>\end{edtable}
% -- where <args> and <entries> are usual arguments and entries
% for <stdtable>. So an example is:
%   \begin{edtable}{tabular}{cc}
%     left upper & right upper \\ left lower & right lower
%   \end{edtable}
% This produces just what <stdtable> does in an extra line,
% only adding line numbers in the margin and processing 'ednotes'
% commands in the entries appropriately.
% (b) Let <stdarray> be an "array environment" like -- standard
% LaTeX's 'array'! "Like" here means (i) ... analogously to
% <stdtable> above. (ii) "Text" ... oh, sorry, this is not clear
% to me at present, and I am in a hurry.                %% TODO
% (iii) Nothing from the 'amsmath' package seems to work here,
% sorry, I have tried a lot ... (iv) For standard LaTeX's
% 'eqnarray', it is better to try the 'linenomath' environment
% of 'lineno.sty' [with package option 'mathlines']. Its
% modifications in 'amsmath' produce (at best) a spurious line
% number with the 'linenomath' environment (up to now).

```

```

% -- Now the syntax is:
%   \begin{edtable}[<$$$>]{<stdarray>}
%     <args><entries>\end{edtable}
% -- where <args> and <entries> are usual arguments and entries
% for <stdarray>. <$$$> can be one of '$' or '$$'. Indeed, the
% <stdtable> syntax above (without [<$$$>]) *does not work*
% inside $...$ or $$...$$$. -- An example:
%   \begin{edtable}[$$]{array}{cc}
%     a_{11} & a_{12} \\ a_{21} & a_{22}
%   \end{edtable}
% Now, this produces just what <stdarray> does in an extra line
% etc. as with <stdtable>. However, \linelabel and 'ednotes.sty'
% footnotes may need the 'mathrefs' option of 'lineno.sty'. For
% the difference between '['$']' and '['$$']', see below.
%
% 2. When working with 'ednotes.sty', in
%   \Anote{L1\<L2>\>L3}{NOTE}
% L2 may contain &'s and \\'s, but L1, L3 must not! Analogously
% for \Bnote, etc., \Anotelabel...\donote..., etc. -- Well this
% holds for <stdtable>, hardly for <stdarray> ...      %% TODO
%
% 3. On positioning: You may have wondered about 'extra line'
% above. This means that 'edtable' starts a new line at
% \begin{edtable} and at \end{edtable}.      %% TODO: sure!?
% (a) It should be placed within a 'center', 'flushleft', or
% 'flushright' environment for proper (vertical) spacing, but
% also works without. However, with <stdarray> and optional
% parameter '$$' of 'edtable' (i.e., \begin{edtable}[$$]...),
% you can obtain the usual math display spacing *within a
% paragraph*; especially, the vertical space is less when the
% previous line is short ... and so on.
% (b) Horizontal positioning of line numbers (usually) needs a
% second run (after changing a table)! %% TODO: automatic warning.
% (For wizards: It may fail if some of \leftskip, \rightskip,
% \linewidth, and \@totalleftmargin are used in an unusual way.)
% A <dimen> register \ETextraoffset is provided whose value is
% Opt by default and which additionally moves line numbers
% to the left (right) if given a positive (negative) value.
%                                     %% TODO: any use?
%
% *Package options:*
%
% 1. Option 'longtable' adjusts the 'longtable' environment
% defined by David Carlisle's longtable.sty for use with
% 'lineno.sty' and 'ednotes.sty'. The option makes 'longtable'
% environments appear with line numbers in the margin, according

```

```

% to 'lineno.sty', and process 'ednotes.sty' commands if line
% numbering is active according to 'lineno.sty'.
% [We maintain an alternative package with just this function
% in a slightly different implementation.] %% -> ulnltab.sty.
% Lemmas may go across table entries as with 'edtable' (see above).
% ---There might be options like 'supertabular' for adjusting
% other tabular environments that cannot be handled by the
% 'edtable' environment provided here---they have not been
% implemented yet! %% TODO
%
% 2. Option 'nolongtablepatch' avoids loading/asking for
% 'ltabptch.sty'. I.e.: according to LaTeX bugs database,
% tools/3180 and tools/3485, there have been problems with
% vertical spacing around 'longtable' environments. By default
% the present package loads our 'ltabptch.sty' or asks for it.
% Option 'nolongtablepatch' overrides this. This is useful when
% you don't want to have the patch, especially when you use an
% "emergency stop" installation of TeX.
%
% *Wizard interface:*
% Macros \@ET@makeLineNumber, \@ET@use@outerhook,
% \@ET@execute@outerhook, \@ET@ampnotes \@ET@startlinewith,
% \@ET@trivialize@linelabel are provided as tools for adjusting
% tabular environments for use with 'lineno.sty' and
% 'ednotes.sty'. \@ET@step@linenumber is \let \stepLineNumber
% (from 'lineno.sty'), but could be used as a hook for
% something different. See Environment 'edtable' and Option
% 'longtable' below for examples of application.
%                                     %% TODO: specification here.
%
%
% %% * Acknowledgements: *
%
% Stephan I. B"ottcher told us how to do it in extensive discussion
% and by providing some first code lines. We changed these essentially
% in some respects, but kept his general ideas and some parts of his
% macros, the latter even without knowing what we are doing.
%
% v1.3 is due to a request by Martin Brandenburg.
%
% * Now for internals: *
%
\NeedsTeXFormat{LaTeX2e}[1994/12/01]
% 1994/12/01: \newenvironment* etc. %% TODO: more recent needed?
\ProvidesPackage{edtable}[\filedate\space v\fileversion\space
arrays with lineno + ednotes (ul)]

```

```

%
% Alternative ideas for implementation:
% 1. There is a German package 'TABMAC' enhancing 'EDMAC' (cf.
% documentation of 'ednotes.sty'). We could have rewritten its
% macros so it would work with 'lineno.sty' and 'ednotes.sty'
% in place of 'EDMAC'. [TODO: "tabmac.sty"]
% 2. We redefine 'longtable' by Option 'longtable' because
% there seems to be only one reasonable use of the 'longtable'
% environment in the course of a critical edition. This may be
% different for environments like 'array' and 'tabular' which
% can be used within text lines. Therefore, these environments
% are not redefined.
% 3. One might use \everycr, however: (a) it is executed
% before the first row, (b) it is executed in fake lines that
% 'longtable' uses.
% 4. As an alternative to \everycr, there is the approach of
% redefining \cr and \crrc for setting \noalign. This needs
% redefining \@tabularcr etc.---not nice. We use this approach
% here for 'longtable' which uses a stretching \tabskip.
% For \tabskip=Opt, we attach line numbers by a template.
%
% \RequirePackage{lineno}[2004/10/06]
% Wanted to check lineno version--causes unknown option error.
% See LaTeX bug latex/3730.

% Options:

%% TODO: underful page with 'longtable.sty'!?
\let\if@ET@longtable\iffalse % \newif\if@ET@longtable@
\DeclareOption{longtable}{\let\if@ET@longtable\iftrue}
\let\if@ET@ltabptch\iftrue
\DeclareOption{nologtablepatch}{\let\if@ET@ltabptch\iffalse}
\ProcessOptions

% Redefine \longtable if option:
\if@ET@longtable
% Stephan's direction for attaching a line number to each row
% is using \noalign in the course of \\.
% However, (1) the user should not worry about closing the table
% with \ or without, and (2) the line number thing should not
% happen twice if \ is the last token before \end{longtable}.
% Our solution: attach something to the beginning of \endlongtable
% which attaches line number unless an unsuccessful \ has done it.
% This thing is activated by each row start and turned off by \.
% Since the switch at row start may happen to be in a pbox,
% let it act globally on \endlongtable. (The \crrc at the beginning

```

```

% of \endlongtable must not be changed directly, since original
% \crrc may be required in table entries using \oalign etc.)
%
\RequirePackage{longtable}%
% \IfFileExists{longtable.sty}{\RequirePackage{longtable}}%
% {\RequirePackage{longtbl}}}%
% For Atari problem, it suffices to rename 'longtable.sty'
% into 'longtabl.sty'.
%
% Patch for tools/3180 and tools/3485 of LaTeX bug database:
\if@ET@ltabptch
\IfFileExists{ltabptch.sty}{\RequirePackage{ltabptch}}{%
\PackageError{edtable}{%
ltabptch.sty (for improving spacing around\MessageBreak
longtable) missing! Be sure to use it always\MessageBreak
or never!%
}{%
To omit ltabptch.sty *and* escape this error,\MessageBreak
use package option 'nolongtablepatch'.%
}%
}
\fi
\let\@ET@longtable\longtable
\def\longtable{%
\ifLineNumbers
\expandafter\@ET@longtable
\else
\let\@ET@sw@cr\@ET@crrc % ... in \endlongtable.
\expandafter\@ET@longtable
\fi
}
\def\@ET@longtable{%
% Since we have made it anyway, we use the method of redefining
% \halign for inserting the activating row start as well.
% However, redefinition must be repeated before every \LT@bchunk.
% \longtable and \LT@get@widths are good places for this.
\@ET@startlinewidth\@ET@sw@cr@on
\@ET@trivialize@linelabel
\@ET@use@outerhook
\@ET@ampnotes
\let\LT@tabularcr\@ET@LT@tabularcr
\expandafter\def\expandafter\LT@get@widths\expandafter
{\LT@get@widths\@ET@startlinewidth\@ET@sw@cr@on}
% Admittedly, we could make it less of a hack by using @{...}
% ---we could then leave \LT@get@widths untouched.
\@ET@longtable

```

```

}
\def\@ET@sw@cr@on{\global\let\@ET@sw@cr\@ET@cr@attach}
% We are hacking a longtable version offering
% \def\LT@tabularcr{%
%   \relax\iffalse{\fi\ifnum0='}\fi
%   \@ifstar
%     {\def\crrc{\LT@crrc\noalign{\nobreak}}\let\cr\crrc
%     \LT@t@bularcr}%
%     {\LT@t@bularcr}}
% We need a redefinition of \cr which is not overridden by \@ifstar:
\def\@ET@LT@tabularcr{%
  \relax\iffalse{\fi\ifnum0='}\fi
  \def\cr{\@ET@sw@cr}%
  % So \crrc is affected by change of \@ET@sw@cr, cf. below.
  \let\crrc\cr
  \@ifstar
    {\gdef\@ET@sw@nobreak{\nobreak
      \global\let\@ET@sw@nobreak\relax}%
    {\def\cr{\@ET@sw@cr\noalign{\nobreak}}\let\cr\crrc
  % Why didn't this work? %% TODO: try shorter again.
  \LT@t@bularcr}%
  \LT@t@bularcr
  %   {\let\cr\@ET@sw@cr \let\crrc\cr
  %   \LT@t@bularcr}% This accompanied \def\cr... above.
}
% Attach \@ET@sw@cr to beginning of \endlongtable:
\expandafter\def\expandafter\endlongtable\expandafter
  {\expandafter\@ET@sw@cr\endlongtable}
\def\@ET@cr@attach{% Actually attaching line numbers.
  \@ET@crrc\noalign{% Basically Stephan's approach.
% If we were not careful, following box containing line number
% could fool interline glue after longtable, even if tools/3485
% is repaired in some way. This box should have same depth as
% the line composed previously.
  \nobreak %% \@ET@ex... might cause page break. 2003/10/30.
  \setbox\z@\@ET@makeLineNumber
  \ht\z@-\prevdepth \dp\z@\prevdepth \box\z@
  \@ET@step@linenumber
  \global\let\@ET@sw@cr\@ET@crrc % ... if called by \\.
% This also resets the \crrc starting \LT@echunk following
% \@xarraycr or \@yarraycr in \LT@argtabularcr.
% \let...\relax seems to suffice at well, but in case ...
  \@ET@execute@outerhook %% 2003/10/30.
  \@ET@sw@nobreak
%   \@ET@execute@outerhook
}%

```

```

}
\let\@ET@crcr\crcr
\global\let\@ET@sw@nbreak\relax % Just to remind ...
\fi

\let\@ET@step@linenumber\stepLineNumber
% \def\@ET@step@linenumber{\global\advance\c@linenumber\@ne}
\def\@ET@makeLineNumber{\hb@xt@z@{\makeLineNumber}}
%% TODO: export to lineno.sty!?
% Special \halign:
% For 'array' etc., we insert line numbers by a leftmost template.
% @{...} in the last argument of 'array' etc. is difficult for this
% since 'tabular*' has an additional argument. So we redefine
% \halign to put something to the right of the next \bgroup.
% Now, as a macro, \halign would break in an \edef or \xdef.
% Horribly, this danger has become quite real in longtable.sty's
% definition of \LT@bchunk. Only its latest version 4.10 has
% preceded \halign by a \noexpand (for mathtext.sty which
% redefines \halign as well). We need not rely on such a
% provision if we let \halign expand to \the<token register>
% for some token register. However, using \toks@ or \@temptokena
% is neither very safe---might be filled by macro ahead with
% something new. So reserve an own token register.
\newtoks\@ET@toks
\@ET@toks{\@ET@specialhalign}
% v1.3: In 'AMSMath', there are \halign's followed by explicit
% left braces. Thus '\def\@ET@specialhalign#1\bgroup{' broke.
%% TODO ...
\def\@ET@specialhalign{%
  \ifmeasuring@ \expandafter\@firstoftwo
% v1.3 2005/03/04, for 'amsmath'.
  \else \expandafter\@secondoftwo
  \fi
  {\let\halign\@ET@@halign \halign}%
  {\@ifnextchar\bgroup\@ET@replace@arg\@ET@sphalign@to}}
%% TODO: change back, commenting out code above, report
%% error with 'alignat'.
% \@ifnextchar\bgroup\@ET@replace@arg\@ET@sphalign@to}
% If 'amsmath' not loaded (v1.3):
\AtBeginDocument{\@ifundefined{measuring@true}{%
  \let\ifmeasuring@\iffalse}\relax}
\def\@ET@replace@arg#1{%
  \def\@EN@tempa{#1}\def\@EN@tempb{\bgroup}% Corr. after v1.3b.
  \ifx\@EN@tempa\@EN@tempb
    \def\@EN@tempa{\@ET@sphalign@to\bgroup}%
  \else

```

```

    \def\@EN@tempa{\@ET@sphalign@to{#1}}%
% This may be wrong, #1 might be 't' from 'to' ...
    \fi
    \@EN@tempa}
\def\@ET@sphalign@to#1\bgroup{%
    \let\halign\@ET@@halign % Reset for nested arrays.
    \halign#1\bgroup
% \ifmeasuring@\else % For 'amsmath', moved backwards.
    \@ET@startline % [Wizard interface, via \@ET@starlinewith.]
% \fi
}
% Wizard interface:
\def\@ET@starlinewith{% Next token precedes preamble.
% \let\@ET@@halign\halign % Or \AtBeginDocument?
% ... indeed: bad loop with long longtable (\LT@get@widths!?)
\def\halign{\the\@ET@toks}%
\let\@ET@startline
}
\AtBeginDocument{\let\@ET@@halign\halign}
% Or save it at start of environment only
% (don't repeat inside longtable).
%
% Outer hook for inserts: (wizard interface)
\def\@ET@execute@outerhook{% To be placed outside inner mode.
    \@ET@outerhook \global\let\@ET@outerhook\@empty
}
\global\let\@ET@outerhook\@empty % Just to remind: global!
% \@EN@hookfn (ednotes) sends to outer hook:
\def\@ET@use@outerhook{% Wizard interface.
    \def\@EN@hookfn{\g@addto@macro\@ET@outerhook}%
}%% TODO: move last line to 'ednotes', \let\@ET@use...\@empty.
%%      But this requires re-installing both packages
%%      at the same time. See the 'ampnotes' thing as well.
%
% Trivialize \linelabel: (wizard interface)
\def\@ET@trivialize@linelabel{\let\linelabel\@ET@linelabel}
\def\@ET@linelabel{%
    \protected@edef\@currentlabel{\theLineNumber}%
    \label
}
% Change ampersand at \Anote etc.: (wizard interface)
%% 2003/10/31.
% & is changed by \Anote etc. No \begin...\endgroup,
% next \ or & after % note/donote command switches back.
% ---Global change seems to break table setup.
\begingroup

```

```

\gdef\@ET@hideamps{\catcode'\&\active}
\@ET@hideamps
\gdef\@ET@ampnotes{%
  \let&\@ET@hideamp
  %% & would be undefined after \\ in lemma.
  \let\@ET@EN@rnote\@EN@note
  \def\@EN@note{\@ET@hideamps\@ET@EN@rnote}%
  \let\@ET@EN@notelb\@EN@notelabel
  \def\@EN@notelabel{\@ET@hideamps\@ET@EN@notelb}%
}
%% TODO: & and \\ in \@EN@lemmaexpands!?
\endgroup
\def\@ET@hideamp{&}

\newenvironment*{edtable}[2][]{%
% #1 $ or $$, #2 standard environment name.
%% TODO: star version!? cf. lineno.sty's 'numquote'.
  \def\@ET@mode{#1}%
  \def\@ET@currenvir{#2}%
  \ifhmode \ifnum\the\lastpenalty=-\@M\else
% \par must be executed for printing/stopping line numbers:
  \centercr\relax \noindent
  \fi \fi
  \ifvmode \noindent \fi % Otherwise linewidths are indented
% -- however, not recommended.
  \@ET@use@outerhook
  \@ET@trivialize@linelabel
  \@ET@ampnotes
  \@ET@startlinewith\@ET@normal@startline
  \global\advance\c@linenumber\m@ne % Stepping correction.
% (Must come after closing previous paragraph.)
% Calculate offset:
  \global\advance\c@ET@array\@ne
% Saving/calling width of table ('longtable's algorithm).
% Test if there is \@flushglue on the left (center or flushleft):
  \edef\@EN@tempa{\the\@flushglue}%
% ... v1.3: fool this for "$$".
  \in@{$$}{#1\@nil}% \in@{#1}{#2} searches #1 in #2#1 ...
  \edef\@EN@tempb{\the\ifin@\@flushglue\else\leftskip\fi}%
  \ifx\@EN@tempa\@EN@tempb
% Assume \@ET@offset is Opt else here.
  \@ET@offset\linewidth
  \advance\@ET@offset-%
  \@ifundefined\@ET@arraywidth@csn % Shortened for v1.3.
  {\linewidth\G@refundefinedtrue
  \PackageWarningNoLine{edtab}{^^JLine numbers at

```

```

        \@ET@currenvir\space need \jobname.aux}}%
        {\csname\@ET@arraywidth@csn\endcsname}%
% Test if \@flushglue on the right (center):
% ... v1.3: fool it again. Repeat \in@ in case ...
        \in@{${$}}{#1\@nil}%
        \edef\@EN@tempb{\the\ifin@\@flushglue\else\rightskip\fi}%
        \ifx\@EN@tempa\@EN@tempb \divide\@ET@offset\tw@ \fi
\fi
\advance\@ET@offset\@totalleftmargin
\advance\@ET@offset\ETextraoffset % Offset ready.
\setbox\@tempboxa\hbox\bgroup
% v1.3: 'alignat' complains later when this is \vbox instead.
% \vbox\bgroup % Tried in vain.
        \ifx\@ET@mode\@empty\else $\fi
        \csname#2\endcsname
}%
        \csname end\@ET@currenvir \endcsname
        \ifx\@ET@mode\@empty\else $\fi
\egroup
\@ET@step@linenumber % Stepping correction.
\if@filesw
        \immediate\write\@auxout{%
                \gdef\expandafter\noexpand
                \csname\@ET@arraywidth@csn\endcsname
                {\the\wd\@tempboxa}}%
%% TODO: warning if changed!?
\fi
% No automatic line number at array line:
\nolinenumbers
\@ET@mode\ensuremath{\vcenter{\box\@tempboxa}}\@ET@mode % v1.3.
\@ET@execute@outerhook
\ifhmode \@centercr\relax \fi
% \par must be executed for proper restart of printing line numbers
% (think so).
\@endpetrue % Outside \@flushglue environment, avoid indent ahead.
%% TODO: slightly change for math mode around? Or give an error
%% in math mode.
}
%% TODO: make \edtable \outer!?
\def\@ET@normal@startline{%
        \@ET@step@linenumber
        \llap{\@ET@makeLineNumber \hskip\@ET@offset}}%
}
\newdimen\@ET@offset
\newdimen\ETextraoffset
%% TODO: export to lineno.sty!?

```

```

\newcount\c@ET@array
\def\@ET@arraywidth@csn{ET@a\romannumeral\c@ET@array}
%
%% TODO: .dtx
\endinput

%% VERSION HISTORY:
v0.22 2003/01/13 First version, named 'edtab02.sty', sent around,
              together with ednotes.sty.
v0.23 2003/01/22 Added version history.
v0.24 2003/01/27 Copyright notice.
%%% v0.3 2003/03/03 Requires linenox0.sty. %% RETREATED
%% TODO: reconsider, see 'lineno[x].sty'.
v0.25 2003/03/05 Added <ednotes.sty@web.de>.
v0.26 2003/03/23 Added \@ET@startlinewith to wizard command list;
              moved redefinition \LT@get@widths from option code
              into \@ET@longtable so this really happens in
              line number mode only; moved \let\@ET@@halign\halign
              from \@ET@startlinewith to \AtBeginDocument.
v0.27 2003/06/02 Added \ifvmode \noindent \fi to 'edtable' definition;
              2003/06/10 added 'lemma cannot run' to instructions.
v0.28 2003/10/31 \@ET@cr@attach: moved \@ET@execu..., added \nobreak.
              Added \@ET@ampnotes and documentation: now working
              across entries.
v1.0 2004/05/13 'ednotes.sty' etc., updated copyright. Renamed as
              'edtable.sty' for TUGboat article.
              \RequirePackage{lineno}, changed doc. accordingly.
              Removed 'may be released under different name'.
v1.10 2004/07/27 Looking for 'longtabl.sty' for my Atari!
              2004/08/22 Added warning (screen/documentation) concerning
              ltabptch.sty.
              2004/08/23 Added suggestion of option 'nolongtablepatch';
              LPPL v1.3.
v1.2 2004/08/31 Rearranged preamble concerning maintenance,
              removed 'preliminary release'.
              2004/10/06 \newif -> \let...; option 'nolongtablepatch';
              changed documentation accordingly and for
              loading edtable.sty by lineno/ednotes option;
              \let\@ET@step@linenumber\stepLineNumber; use
              \ifLineNumbers.
              2004/10/07 Needed version numbers.
              2004/10/08 ltabptch warning -> error!
              2004/10/11 Disabled \RequirePackage{lineno}[...]; undid
              the 'longtabl.sty' thing from 2004/07/27.
              2004/10/12 latex/3730.
v1.2a 2004/11/07 LPPL v1.3a.

```

v1.2b 2005/01/10 Contact via http.
v1.3b 2005/03/04 Support for environments like ‘array’
environment. The description of ‘edtable’ was
wrong in this respect!
v1.3 2005/03/07 Adaptations in documentation, and extended usage
instructions very much, correcting some
errors as well. Acknowledgement to M. B.
v1.3a 2005/03/09 Corrected numbering in ‘usage’.
v1.3c 2005/03/15 \@centercr\relax, TODO on math mode.
2005/04/09 ‘editory’ -> ‘editorial’.

2.2 ltabptch.sty

```

%% LTabPtch.sty---Uwe L"uck---patch for Longtable.
\def\filedate{2005/01/10} \def\fileversion{1.74d}
%% For David Carlisle's Longtable.sty, version 4.11
%% Fixes tools/3180 (Sebastian Rahtz) and tools/3485:
%% missing/wrong interline glues above/below table.
%%
%% Copyright (C) 2002--2004 Uwe L"uck,
%% http://www.contact-ednotes.sty.de.vu
%% --author-maintained.
%%
%% Usage, no warranty, distribution as in lppl.txt on CTAN
%% (macros/latex/base/lppl.txt).
%%
%% Loading Longtable.sty with options must be done earlier!
%%
\NeedsTeXFormat{LaTeX2e}[1994/05/20] % \CheckCommand
\ProvidesPackage{ltabptch}[\filedate\space v\fileversion\space
  Longtable patch for tools/3180, 3485 (ul)]
%
% The problem(s):
% Sebastian Rahtz (tools/3180) observed 2000/03/05 that there be
% a "spurious blank line" below the longtable. This impression
% may have been due to two spacing problems:
% (1) There is \parskip and some interline glue below longtable,
% while there is no \parskip and no interline glue above
% (without head as specified by \endhead or \firstendhead)
% or just \lineskip 0.0pt (with head---\endhead, \endfirsthead).
% (2) After longtable, \prevdepth is the depth of the last line
% before the longtable (if there is no head) or the depth of the
% head (otherwise). So \prevdepth may be 0pt. By contrast, the
% last table row has depth of at least \dp\@arstrutbox--which
% should rather matter, and this is 3.6pt or more.
% --I have reported something like this as tools/3485, not

```

```

% entirely correctly. Details are presented below \endinput.
%
% Solution presented:
% (1) I think there should be \parskip and usual interline glue
% above, since the same would happen with a table in a center
% environment (e.g.).
% \noindent seems to work fatally; moreover, \LT@start's decision
% whether to enter a new page would ignore \parskip and interline
% glue still needed.
% So emulate interline glue calculation according to TeXbook p. 80
% and add it by \vskip, along with \parskip.
% (This is rather a hack---a proper correction should perhaps not
% "emulate" but place the interlineglue changes of \LT@array inside
% the \vbox \LT@bchunk starts and treat glue between chunks in a
% new way.)
% (2) Set \prevdepth to depth of box 0 before the latter is
% \unvbox'ed (which leaves \prevdepth untouched, TeXbook p. 282)
% in \endlongtable.
%
% I thought David Carlisle would change Longtable according to my
% suggestions. By e-mail from 2003/04/07 however, he finds it
% better not to change Longtable, in order not to change layouts
% of works that have been made using Longtable so far
% (e-Mail 2003/04/08).
%
%% <- TODO: change this when David has changed his mind!
% By the way:
% 1.) There are two successive lines in the Longtable code (v4.11)
% together saying:
%     \prevdepth\z@\global
%     \global\let\LT@setprevdepth\relax
% Isn't the first \global just a typo?
% --Yes--this is David Carlisle's answer in his e-mail
% dating from 2004/05/14.
% 2.) Couldn't the one-column restriction easily be removed
% by using \columnwidth instead of \hsize?
%
% Patching is to override Longtable.sty:
\RequirePackage{longtable}[2004/02/01]
%% TODO: Cf. \CheckCommand below.
% Load earlier on your own for choosing Longtable options!
%
% For (1), we are patching \LT@start, assumed to have been defined
% as follows (Longtable v4.11; sorry we can no longer handle v3.16
% through 4.10):

```

```

\CheckCommand*{\LT@start}{%
  \let\LT@start\endgraf
  \endgraf\penalty\z@\vskip\LTpre
  \dimen@\pagetotal
  \advance\dimen@ \ht\ifvoid\LT@firsthead\LT@head\else\LT@firsthead\fi
  \advance\dimen@ \dp\ifvoid\LT@firsthead\LT@head\else\LT@firsthead\fi
  \advance\dimen@ \ht\LT@foot
  \dimen@ii\vfuzz
  \vfuzz\maxdimen
  \setbox\tw@\copy\z@
  \setbox\tw@\vsplit\tw@ to \ht\@arstrutbox
  \setbox\tw@\vbox{\unvbox\tw@}%
  \vfuzz\dimen@ii
  \advance\dimen@ \ht
    \ifdim\ht\@arstrutbox>\ht\tw@\@arstrutbox\else\tw@\fi
  \advance\dimen@\dp
    \ifdim\dp\@arstrutbox>\dp\tw@\@arstrutbox\else\tw@\fi
  \advance\dimen@ -\pagegoal
  \ifdim \dimen@>\z@\vfil\break\fi
    \global\@colroom\@colht
  \ifvoid\LT@foot\else
    \advance\vsizel-\ht\LT@foot
    \global\advance\@colroom-\ht\LT@foot
    \dimen@\pagegoal\advance\dimen@-\ht\LT@foot\pagegoal\dimen@
    \maxdepth\z@
  \fi
  \ifvoid\LT@firsthead\copy\LT@head\else\box\LT@firsthead\fi\nobreak
%% \nobreak new with Longtable v4.11.
  \output{\LT@output}}
%
% Change it:
\def\LT@start{%
  \let\LT@start\endgraf
  \endgraf\penalty\z@\vskip\LTpre
  \vskip\parskip %% U.L.
% I want to add the interline glue before \pagetotal goes to \dimen@.
% So I move \LT@start's \vsplit here.
%% U.L. start:
  \dimen@ii\vfuzz
  \vfuzz\maxdimen
  \setbox\tw@\copy\z@
  \setbox\tw@\vsplit\tw@ to \ht\@arstrutbox
  \setbox\tw@\vbox{\unvbox\tw@}%
  \vfuzz\dimen@ii
  \ifdim\prevdepth>-\@m\p@
% First we need the maximum of the heights of \tw@ and head row.

```

```

% A little flaw might be here: I am ignoring \Lt@start's
% \@arstrutbox concern below, cf. remark there.
  \@tempkipa % \normalbaselineskip going to enter.
    \ht\ifvoid\LT@firsthead\LT@head\else\LT@firsthead\fi
% \typeout{\@tempkipa=\the\@tempkipa}% TEST
  \@tempkipa-\ifdim\@tempkipa<\ht\tw@\ht\tw@\else\@tempkipa\fi
% \typeout{\@tempkipa=\the\@tempkipa}% TEST
  \advance\@tempkipa-\prevdepth
% \typeout{\string\prevdepth=\prevdepth}% TEST
% \typeout{\@tempkipa=\the\@tempkipa}% TEST
  \advance\@tempkipa\normalbaselineskip
% \typeout{\normallineskiplimit=\the\normallineskiplimit}% TEST
% \typeout{\@tempkipa=\the\@tempkipa}% TEST
  \vskip \ifdim\@tempkipa<\normallineskiplimit
    \normallineskip
  \else
    \@tempkipa
  \fi
\fi
\nointerlineskip % v1.4 prevent head from adding more
%           % (if only negative) glue.
% \prevdepth -1000\p@ % Prevent head from adding more glue (v1.3).
%% U.L. end.
  \dimen@ \pagetotal
  \advance\dimen@ \ht\ifvoid\LT@firsthead\LT@head\else\LT@firsthead\fi
  \advance\dimen@ \dp\ifvoid\LT@firsthead\LT@head\else\LT@firsthead\fi
  \advance\dimen@ \ht\LT@foot
% \dimen@ii\vfuzz
% \vfuzz\maxdimen
% \setbox\tw@\copy\z@
% \setbox\tw@\vsplit\tw@ to \ht\@arstrutbox
% \setbox\tw@\vbox{\unvbox\tw@}%
% \vfuzz\dimen@ii
%
% Remark U.L.: The following four code lines seem strange to me:
% after all, \tw@ contains \@arstrutbox, doesn't it?
% And even if not: why should we need room for another \@arstrutbox?
  \advance\dimen@ \ht
    \ifdim\ht\@arstrutbox>\ht\tw@\@arstrutbox\else\tw@\fi
  \advance\dimen@\dp
    \ifdim\dp\@arstrutbox>\dp\tw@\@arstrutbox\else\tw@\fi
  \advance\dimen@ -\pagegoal
  \ifdim \dimen@>\z@\vfil\break\fi
    \global\@colroom\@colht
  \ifvoid\LT@foot\else
    \advance\vsizel-\ht\LT@foot

```

```

\global\advance\@colroom-\ht\LT@foot
\dimen@\pagegoal\advance\dimen@-\ht\LT@foot\pagegoal\dimen@
\maxdepth\z@
\fi
\ifvoid\LT@firsthead\copy\LT@head\else\box\LT@firsthead\fi\nobreak
%% \nobreak new with Longtable 4.11.
\output{\LT@output}}
%
%
% For (2), we are patching \endlongtable:
% The patch should not change essentials of \endlongtable
% which may have changed when this patch meets longtable.
% We just assume that the final contribution to the main vertical
% list is done by \unvbox0 which is preceded by \LT@start.
% \prevdepth\dp0 can be put in between, it will then
% last till the end (TeXbook pp. 282, 277f.).
\def\@tempa#1\LT@start{#1\LT@start \prevdepth\dp\z@}
\expandafter\expandafter\expandafter \def
\expandafter\expandafter\expandafter \endlongtable
\expandafter\expandafter\expandafter
{\expandafter\@tempa\endlongtable}
%
\endinput

```

DETAILED DIAGNOSIS:

Concerning the question of "bugs" vs. "features", you might reason what features should be aimed at.

%% TODO: This can be shortened when David agrees.

(A) If there is \parskip below a longtable, there should be \parskip above as well--shouldn't it?

(B) Interline glue above should (in general) depend on the same values of \baselineskip and \lineskip as below---OK?

(C) Interline glue below a longtable should depend on the depth of the last row, not on the depth of the head or of the last line above the longtable--OK?

The recent versions of longtable.sty have not satisfied any of these three demands.

Concerning (A), \parskip appears below the longtable, but not above.

Concerning (B), (i) no interline glue appears above if there is no head, (ii) otherwise, only zero interline glue appears.

Concerning (C), the interline glue below the longtable is

calculated using the depth of (i) the last line above the longtable as `\prevdepth` when there is no head or of (ii) the head otherwise. (Thus I was wrong earlier when I claimed that `\prevdepth` were `Opt` after longtable. This only holds in the previous case (i) when the last line above the longtable has zero depth.)

You can observe this by playing with the demonstration file `ltabptch.tex` in CTAN folder `macros/latex/contrib/ltabptch`.

Reasons: For contributing a head to the main vertical list, longtable uses `\copy` or `\box`, which yields a `<box>` according to TeXbook p. 278. Rows are contributed by `\unvbox`. Now, violation of (A) is due to the fact that neither `\copy` or `\box` of the head nor the `\unvbox` for table rows leads to execution of an `\indent` or `\noindent` (TeXbook pp. 282f., see also `<horizontal command>`).

Violation of (B) is due either to (i) the fact that `\unvbox` is no `<box>` (TeXbook p. 282/278) or to (ii) the fact that at `\copy` or `\box` `\baselineskip` and `\lineskip` are `Opt`.

Violation of (C) is due to the fact that `\unvbox` does not change `\prevdepth` (TeXbook p. 282).

As to recognizable effects:

Violation of (A), of course, has very little effect in general since `\parskip` is `Opt` plus `1pt` usually. This is hardly recognizable in the presence of the `\bigskipamount` above and below a longtable.

Violation of (B) results in missing appropriate interline glue above, which often should be `3.6pt` or more. This may rather be recognizable and may contribute to the impression that there even is a spurious blank line below the longtable (this is what Sebastian Rahtz reported in `tools/3180`).

For the previous as well as for the details and the effects of violation of (C), consider the algorithm for calculating interline glue on p. 80 of the TeXbook. If there is no head, and the depth of the last line before the longtable is `Opt`, the interline glue below the longtable is `\baselineskip` minus the height of the first line after the longtable. The interline glue *should be* `\baselineskip` minus height of following line *minus* depth of last table row--if this depth is not too large (depending on `\lineskiplimit`). This depth is at least `3.6pt`. So the interline glue is often by `3.6pt` or more greater than is appropriate. Considering the missing interline glue above the longtable and the `\parskip` below, the glue after the longtable is by `6.2pt` (or more) plus

1pt larger than the glue before. Due to the shrink component of the surrounding \bigskipamount, the glue following the longtable may be nearly twice as large as the glue before. ---Usually, violation of (C) has no effect at all. Namely, there is a head usually, and its depth is usually the same as the depth of the last row, namely \dp\@arstrutbox.

%% VERSION HISTORY:

v1.7 2003/01/07 Sent around 2003/01/13 with first release of ednotes.sty. Sent to David Carlisle. Earlier versions were sent to Frank Mittelbach and the team.

v1.71 2003/01/22 Added version history.

v1.72 2003/01/27 Changed copyright notice.

v1.73 2004/05/13 Adapted to Longtable v4.11; new copyright; longtable -> Longtable (selectively). Added 'I have ... 3485'.

v1.74 2004/08/05 Added '---Yes---...'.
2004/08/21 Typo fix for 'problem'; added report on 2003/04/08.
2004/08/23 Corrected and extended diagnosis, sent to CTAN.

v1.74b .../08/23 '---' -> '--'; added that (C) usually doesn't matter.

v1.74c .../08/31 'author-maintained'.

v1.74d 2005/01/10 Contact via http.

3 \linelabel and notes from *math* mode: ednmath0.sty

%% Macro package 'ednmath0.sty' for LaTeX2e,
%% copyright (C) 2004 Uwe L\"uck,
%% <http://www.contact-ednotes.sty.de.vu>
%% --author-maintained;
%% math support for 'lineno.sty' and 'ednotes.sty'.
%%
\def\fileversion{v0.2b} \def\filedate{2005/01/10}
%% This program can be redistributed and/or modified under the
%% terms of the LaTeX Project Public License distributed from
%% CTAN archives in directory macros/latex/base/lppl.txt; either
%% version 1.3a of the License, or any later version.
%% The latest version of this license is in
%% <http://www.latex-project.org/lppl.txt>
%% There is NO WARRANTY.
%% This code is very EXPERIMENTAL!

```
%%
%% Please report bugs, problems, and suggestions via
%%
%%   http://www.contact-ednotes.sty@web.de
%
%% * MAIN FEATURE *
%
% lineno.sty's \linelabel and ednotes.sty's commands are enabled
% to work in math mode if it's "entered in outer mode"
% (including 'displaymath' and 'equation' environments).
% (lineno.sty is the package by Stephan Boettcher.)
% They will even work in tabular environments that are adjusted
% to notes by package 'edtable.sty'.
%
% CAVEATS:
% -- Does not work yet in environments like LaTeX's
% 'eqnarray'. (This could probably be repaired along the lines
% of Edtable.sty--we're short of time and will try later.)
% -- Useful error messages when (i) math mode is entered from
% inner mode or when (ii) a math display gets not line number
% are missing at present.
%
%% * USAGE: *
%
% * Most simple: *
% --If you are working with ednotes and want to use its
% commands in math mode, load ednotes.sty--version 0.8
% onwards--with its package option 'mathnotes'.
% --If you don't work with ednotes, only with lineno, you
% get the main feature of making \linelabel work in math mode
% by loading lineno.sty--version 4.1 onwards--with its
% package option 'mathrefs'.
%
% * Switch off and on: *
% To reduce danger resulting from missing error messages
% ("caveat" above), you may switch these new math facilities
% off by \NoNotesToMath where you don't expect to need them.
% You may switch them on again by \NotesToMath where you want
% to use them, being aware of the danger. Both commands work
% locally, so you can replace one of them by enclosing it in
% a group. E.g., even, after \NoNotesToMath you can use an
% environment as follows:
%   \begin{NotesToMath}
%     <text>
%   \end{NotesToMath}
% (I am not quite sure that this is useful.)
```

```

%
% * Customize ellipsis: *
% ednotes' \lemmaellipsis is changed to expand to
% \mathlemmaellipsis when entering math, and this is preset
% to be LaTeX's \mathellipsis. (This is three dots as
% \mathinner.) You can change this by redefining
% \mathlemmaellipsis, e.g.:
% \renewcommand{\mathlemmaellipsis}{\cdots}
% If you need \cdots as the ellipsis at a single place only,
% you may, of course, use the '<...>' option of \<, e.g.:
% $ x = \Anote{a\<<\cdots>bcd\>e}{Indeed?} - y $
%
% * Customize note mode: *
% For variant readings, you may want that the note is
% usually set in math mode--so you may want that you
% needn't type the dollar signs in the note text.
% Note that you can do this by customizing \notefmt,
% and you can do this by customizing \Anotefmt (e.g.)
% to have this feature for \Anote only.
%

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{ednmath0}[\filedate\space\fileversion\space
  math support for lineno/ednotes (ul)]
%
%% User commands:
\def\NotesToMath{\let\LN@mathhook\LN@labelinmath
  \@bsphack \@esphack
% For \begin{NotesToMath}
}
\def\NoNotesToMath{\@bsphack
  \def\LN@mathhook{\@parmoderr\@gobble}%
  \@esphack
}
\def\endNotesToMath{\@bsphack\@Esphack}
\let\endNoNotesToMath\endNotesToMath
%
%% Core code for lineno.sty:
\@ifundefined{LN@postlabel}{%
  \PackageError{ednmath0}{%
    Bad lineno.sty version%
  }{%
    lineno.sty from 2004/08/16 or later
    must be loaded earlier.%
  }%
}{%

```

```

\def\@LN@labelinmath#1{%
  \ifmmode
    \@LN@postlabel{#1}%
  \else
    \@parmoderr
  \fi
}
}
%
%% Core code for ednotes.sty:
\@ifundefined{@EN@note}{%
% v0.01 sent a warning in this case. Considered superfluous now.
}%
\def\@EN@themathlemmatag{%
  \ifmmode
    \toks@\expandafter{\@EN@lemmatag}%
    \edef\@EN@lemmatag{%
      $%
        \def\noexpand\lemmaellipsis{%
          \noexpand\mathlemmaellipsis}%
        \the\toks@
      $%
    }%
  \else
    \expandafter \def \expandafter \@EN@lemmatag
    \expandafter {\expandafter $\expandafter
    \def \expandafter \lemmaellipsis \expandafter {%
    \expandafter \mathlemmaellipsis \expandafter }%
    \@EN@lemmatag $}%
  \fi
}
%
% To be sure, \lemmaellipsis doesn't need to be changed when
% ednotes '\<...\>' feature is not used. Though I prefer to
% use one hook only in ednotes for both situations, with and
% without '\<...\>'.
%
% The final \unskip in ednotes' \@EN@lemmatag would undo a final
% \quad. That's OK: outside math the same happens.
% In v0.01, \NoNotesToMath undid ednotes changes for math mode.
% However, re-appearance of \linelabel error messages suffices.
%
% Now add lemma switch to the left of \[No]NotesToMath:
\toks@\expandafter{\NotesToMath}
\edef\NotesToMath{%
  \let \noexpand\@EN@mathlemmatag \noexpand\@EN@themathlemmatag
  \the\toks@
}

```

```

% \typeout{\string\NotesToMath: \meaning\NotesToMath}
\toks@\expandafter{\NoNotesToMath}
\edef\NoNotesToMath{%
  \let \noexpand\@EN@mathlemmatag \relax
  \the\toks@
}
% \typeout{\string\NoNotesToMath: \meaning\NoNotesToMath}
}
% We need no extra device for a choice for users whether the *note*
% should be set in math mode or in horizontal mode by default
% (which might depend on the kind ["layer"] of notes).
% This can be done already by customization of ednotes' \notefmt.
% However, we might change ednotes' default \notefmt to default
% \renewcommand*{\notefmt}[1]{\$#1\$}
%
\let\mathlemmaellipsis\mathellipsis
%% TODO: Since when has LaTeX provided \mathellipsis?
%% -> \Needs...
%
% Default:
\NotesToMath
%
\endinput

%% TODO: Without \linenumberdisplaymath, in displaymath,
%% an error should be shown. Use, e.g., that in a displaymath
%% \ifinner is false.
%% TODO: E.g., by changing \everymath, perhaps can be warned
%% that the math group is in a box already, so the vertical
%% items will get lost.
%% TODO: Adjust 'eqnarray' (in Edtable?) as well.

%% VERSION HISTORY:
v0.01 2004/08/16 First version, sent to Christian.
v0.02 2004/08/16 Considerably simplified for ednotes.
      2004/08/19 Added ellipsis stuff, documentation, and
      instructions. Uncapitalized package names.
      Added \end[No]NotesToMath.
      2004/08/20 Added \@bsphack and \@esphack; corrected
      ednotes extension (too much deleted, completely
      wrong), introducing \@EN@themathlemmatag.
v0.02b .../08/31 Rearranged preamble concerning maintenance.
v0.1 2004/09/20 Removed mentions of 'linenox0.sty'.
v0.2 2004/10/07 Removed another mention of 'linenox0.sty';
      Instructions: 'lineno' or 'ednotes.sty' option.
v0.2a 2004/11/07 LPPL v1.3a.

```

v0.2b 2005/01/10 Contact via [http](http://).

4 Extended line number references: *vplref.sty*

vplref.sty is input through the *lineno* package option *addpageno*. This adds page numbers to line number references to distant sides—using the *varioref* package from the L^AT_EX distribution.

```
%% 'vplref.sty'
%% -- extended line number referencing with lineno.sty.

\def\filedate{2005/04/25} \def\fileversion{0.2a}

%% Copyright (C) 2004, 2005 Uwe Lueck,
%% http://contact-ednotes.sty.de.vu --author-maintained
%% -- support of lineno.sty for varioref.sty.

%% This file can be redistributed and/or modified under
%% the terms of the LaTeX Project Public License; either
%% version 1.3 of the License, or any later version.
%% The latest version of this license is in
%% http://www.latex-project.org/lppl.txt
%% We did our best to help you, but there is NO WARRANTY.

%% USAGE:
%
% \vpagelineref{<label>} expands to
%
% a) \ref{<label>}
%    -- if on same page as \linelabel{<label>}
%
% b) \LineWithPage{<label>} -- otherwise.
%
% \LineWithPage{<label>} expands -- by default -- to
%
% \pageref{<label>}\ref{<label>}
%
% This can be customized by editing
%
% \renewcommand*\LineWithPage[1]{\pageref{#1}\ref{#1}}
%
% in your document preamble, after vplref.sty has been loaded
% (which may have happened through lineno.sty with option
% 'addpageno').
```

```

%% IMPLEMENTATION:

\NeedsTeXFormat{LaTeX2e}[1994/12/01] %% \Declare...*
\ProvidesPackage{vplref}[\filedate\space v\fileversion \space
    page-line cross-refs] %% UL 2011/02/13

\AtBeginDocument{\RequirePackage{lineno,varioref}}

%% Anderer Ansatz: GPNo (\FirstOnPage)

\DeclareRobustCommand* \vpagelineref [1]{%
% \def\reftextcurrent{\lineref{#1}}%% First vpageref arg.
  \let\reftextfaraway\LineWithPage
  \def\reftextafter{\reftextfaraway{#1}}%
  \let\reftextbefore\reftextafter
  \let\reftextfaceafter\reftextafter
  \let\reftextfacebefore\reftextafter
%% <- Looks somewhat stupid, but varioref.sty has its merits
%% as compared with the mechanism in ednotes.sty.
  \pageref[\ref{#1}][{#1}%% The robust alternative.
%% Here and with \LineWithPage, \lineref seems more appropriate
%% than \ref, but it produces errors when labels have not been
%% defined. This seems to be an incompatibility with lineno.sty.
}

%% Customizable format for different page:
\newcommand*\LineWithPage[1]{\pageref{#1}.\ref{#1}}

\endinput

VERSION HISTORY:
v0.1 2004/10/19 First, sent to Sergei Mariev.
v0.11 2004/10/19 Fit to recent varioref version;
sent to Sergei.
v0.2 2005/04/25 \Require... \AtBeginDocument.
v0.2a 2011/02/13 add. caption to \ProvidesPackage

```