

Package `quotes`^{*}

F. Bosisio

E-mail: `fbosisio@bigfoot.com`

1997/12/20

Abstract

Documentation for the package `quotes`.

1 Introduction

This package simplifies the use of double-quotes.

2 Double quotes

With this package, the character “ ” generates the correct double-quote, i.e. the sequence `<< " text " >>` generates `<< " text " >>`, so that this character can be used both for opening and closing the double-quotes (provided that it is *always* used).

^{*}This is version 2.2, last revised 1997/12/20; documentation date 2005/04/09

3 Implementation

```
1 %%
2 \NeedsTeXFormat{LaTeX2e}[1995/12/01]
3 \ProvidesPackage{\FileName}[\filedate\space v\fileversion\space\filedesc]
```

- Quotes** The command “\@VIRGOLETTE” is defined to print an open or close double-quotes alternatively, so that they are always right. Moreover, the double-quotes are always printed in upright-shape, since they looks better.

```
4 %%
5 \newif\if@virgolette\@virgolettetfalse
6 %%
7 \newcommand{\@VIRGOLETTE}{%
8 \if@virgolette%
9   \@virgolettetfalse%
10  \textup{''}%
11 \else%
12  \@virgolettetrue%
13  \textup{''}%
14 \fi%
15 }
```

Then the character “ ” is associated to the command “\@VIRGOLETTE” just defined, so that you just have to type this character in order to get the right double-quotes. This trick has been adapted from the doc package, but perhaps it may be done in a better way.

```
16 \@makeother " %% Can this command be eliminated ?
17 \begingroup
18  \catcode`\~\active  \lccode`\~`\"%
19  \lowercase{%
20  \global\expandafter\let
21    \csname ac\string\"\\endcsname\%
22  \gdef~{\@VIRGOLETTE}}%
23 \endgroup
24 \global\catcode`\~\active
25 %
```

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| | | | | | | | |
|--------------------------------|-------------------------|------------|----|-----------------------------|--------------------------|-------------------------------|--------|
| Symbols | <code>\endcsname</code> | | 21 | <code>\let</code> | | 20 | |
| <code>\"</code> | | 18, 21, 24 | | <code>\endgroup</code> | | 23 | |
| <code>\@VIRGOLETTE</code> | 7, 22 | | | <code>\lowercase</code> | | 19 | |
| <code>\@makeother</code> | ... | 16 | | <code>\expandafter</code> | .. | 20 | |
| <code>\@virgolettefalse</code> | | | | F | | <code>\NeedsTeXFormat</code> | . 2 |
| | | | | <code>\fi</code> | | 14 | |
| | | | | | <code>\newcommand</code> | | 7 |
| <code>\@virgolettettrue</code> | 12 | | | <code>\filedate</code> | | 3 | |
| <code>\~</code> | | 18 | | <code>\newif</code> | | 5 | |
| | | | | <code>\filedescr</code> | | 3 | |
| | | | | <code>\FileName</code> | | 3 | |
| A | | | | P | | | |
| <code>\active</code> | | 18, 24 | | <code>\fileversion</code> | ... 3 | <code>\ProvidesPackage</code> | 3 |
| B | | | | G | | Q | |
| <code>\begingroup</code> | ... | 17 | | <code>\gdef</code> | | 22 | |
| | | | | <code>\global</code> | | 20, 24 | |
| C | | | | I | | S | |
| <code>\catcode</code> | | 18, 24 | | <code>\if@virgolette</code> | 5, 8 | <code>\space</code> | |
| <code>\csname</code> | | 21 | | | | <code>\string</code> | |
| E | | | | | | | 3 |
| <code>\else</code> | | 11 | | <code>\lccode</code> | | 18 | |
| | | | | <code>\textup</code> | | <code>\textup</code> | 10, 13 |
| L | | | | | | T | |

Change History

| | | | |
|------|--|--|---|
| v0.1 | | v2.0 | |
| | General: First release (basic accents-command) 1 | General: Separated from package “quotes” 1 | |
| v0.2 | | v2.1 | |
| | General: Added double- quotes and extended-chars 1 | General: Added copyright notice and changed ad- dresses 1 | |
| v1.0 | General: Documentation added 1 | v2.2 | |
| | | | General: Usage of the double-quote character (“) avoided 1 |
| v1.1 | General: Fixed a bug in the options 1 | | |