

# The **flexisym** package

Authors: Michael J. Downes, Morten Høgholm  
Maintained by Morten Høgholm, Will Robertson  
Feedback: <https://github.com/wspr/breqn/issues>

2019/10/15 0.98g

## User's guide

For now, the user's guide is in breqn.

## Implementation

### 1 flexisym

```
1 <*package>
2 \RequirePackage{expl3}[2009/08/05]
3 \ProvidesExplPackage{flexisym}{2019/10/15}{0.98g}{Make math characters macros}
4
5 \edef\do{%
6   \noexpand\AtEndOfPackage{%
7     \catcode\number`'=\\number\catcode`\
8     \relax
9   }%
10 }
11 \do \let\do\relax
12 \catcode`'=12
13 \let@\sym@\gobble
14 \DeclareOption{robust}{%
15   \def@\sym#1{%
16     \ifx\protect\@typeset@protect \else\protect#1\exp_after:wN\use_none:n\fi
17   }%
18 }
```

The math groups (mg) here relate to \textfontn.

```
19 \def\mg@bin{2}{} binary operators
20 \def\mg@rel{2}{} relations
21 %%\def\mg@nre{B}{} negated relations
22 \def\mg@del{3}{} delimiters
```

```

23 %%\def\mg@arr{B}%
24 \def\mg@acc{0}%
25 \def\mg@cop{3}%
26 \def\mg@latin{1}%
27 \def\mg@greek{1}%
28 \def\mg@Greek{0}%
29 %%\def\mg@bflatin{4}%
30 \def\mg@Bbb{B}%
31 \def\mg@cal{2}%
32 %%\def\mg@frak{5}%
33 \def\mg@digit{0}%

```

This is how we insert mathchars. The command has three arguments: class, fam and slot position and so it is always given as hexadecimal. This way of separating things should make it easier to get this to work with XeTeX et al. which have many more slot positions

```

34 \cs_set_protected:Nn \math_char:NNn {
35   \tex_mathchar:D \__int_eval:w "#1#2#3 \__int_eval_end:
36 }

```

Delimiters and radicals are similar except here we have both small and large variant. Radicals have no class.

```

37 \cs_set_protected:Nn \math_delimiter:NNnNn {
38   \tex_delimiter:D \__int_eval:w "#1#2#3#4#5 \__int_eval_end:
39 }
40 \cs_set_protected:Nn \math_radical:NnNn {
41   \tex_radical:D \__int_eval:w "#1#2#3#4 \__int_eval_end:
42 }
43 \cs_set_protected:Nn \math_accent:NNnn {
44   \tex_mathaccent:D \__int_eval:w "#1 #2 #3 \__int_eval_end: {#4}
45 }
46
47 \let\sumlimits\displaylimits
48 \let\intlimits\nolimits
49 \let\namelimits\displaylimits

```

TEX defines eight types of atoms.

0. Ordinary
1. Operators
2. Binary
3. Relation
4. Open
5. Close
6. Punctuation
7. Inner

TeX defines eight math classes.

0. Ordinary
1. Operators
2. Binary
3. Relation
4. Open
5. Close
6. Punctuation
7. Variable family

flexisym/breqn extends this to types of classes.

0. Ordinary: (Ord), Bidirectional delimiters (DeB), Radicals (Rad), Accented items (Acc)
1. Operators: Cumulative Operators sum-like (COs), Cumulative Operators integral-like (COi)
2. Binary: (Bin)
3. Relation: (Rel), Arrow delimiters (DeA)
4. Open: (DeL)
5. Close (DeR)
6. Punctuation: (Pun)
7. Variable family: (Var)

Here's an overview of what we are about to do. Math chars of each type as defined by us need a basic operation for inserting it. We will call that function `\math_bsym_{<type>}:Nn`. Next there are compound symbols for each type which we name `\math_bcsym_{<type>}:Nn`. Also, there is inline mode and display mode which are different. We will call them for `\math_isym_{<type>}:Nn` `\math_icsym_{<type>}:Nn` for inline mode and `\math_dsym_{<type>}:Nn` and `\math_dcsym_{<type>}:Nn`. The code uses the terms `\math_sym_{<type>}:Nn` and `\math_csym_{<type>}:Nn` for the current meaning of things. First up the basic definitions. #1 is the math group it is from and #2 is the slot position.

```
50 \cs_new:Npn \math_bsym_Ord:Nn {\math_char:NNn 0 }% \m@Ord
51 \cs_new:Npn \math_bsym_Var:Nn {\math_char:NNn 7 }% \m@Var
52 \cs_new:Npn \math_bsym_Bin:Nn {\math_char:NNn 2 }% \m@Bin
53 \cs_new:Npn \math_bsym_Rel:Nn {\math_char:NNn 3 }% \m@Bin
54 \cs_new:Npn \math_bsym_Pun:Nn {\math_char:NNn 6 }% \m@Pun
```

```

55 \cs_new:Nn  \math_bsym_COs:Nn { \math_char:Nnn 1 #1 {#2} \sumlimits }% \m@COs
56 \cs_new:Nn  \math_bsym_COi:Nn { \math_char:Nnn 1 #1 {#2} \intlimits }% \m@COi
57 \cs_new:Nn  \math_bsym_DeL:Nn { \math_sd_del_aux:Nnn 4 #1{#2} }% \m@DeL
58 \cs_new:Nn  \math_bsym_DeR:Nn { \math_sd_del_aux:Nnn 5 #1{#2} }% \m@DeR
59 \cs_new:Nn  \math_bsym_DeB:Nn { \math_sd_del_aux:Nnn 0 #1{#2} }% \m@DeB
60 \cs_new:Nn  \math_bsym_DeA:Nn { \math_sd_del_aux:Nnn 3 #1{#2} }% \m@DeA
61 \cs_new:Nn  \math_bsym_Rad:Nn { \math_sd_rad_aux:Nn #1{#2} }% \m@Rad
62 \cs_new:Npn \math_bsym_Acc:Nn #1#2#3#4 {\mathAccent:Nnn #1#2{#3}{#4}}% name is wrong
63

```

Next is somewhat complicated internally. The way it is done is that delimiters and radicals need information about the smallest version of the symbol. If this smallest delimiter (SD) is defined, then use it. We have these functions to help us return the number. Extract the numbers to use and stick a function in front of it.

Code changed because now we require the smallest delimiter to be defined (it may be the same, no problem in that). So the two arguments present in `\math_bsym_DeL:Nn` are the location of extensible version (where the font will do the rest for us automatically). For each delimiter, a pointer is defined using the extensible characters family and slot as name and value equal to family and position of the smallest version. For ( in standard L<sup>A</sup>T<sub>E</sub>X this is `{del}{00}` and `{OT1}{28}` respectively. Hence, `\math_bsym_DeL:Nn \mg@del {00}` must expand to `\math_delimiter>NNnNn 4 \mg@OT1 {28}\mg@del{00}`. So first expand away to get to the smallest version. Then call next function which shuffles the arguments around.

```

64 \cs_set:Npn \math_sd_del_aux:Nnn #1#2#3{
65   \exp_args:Nf \math_sd_del_auxi:nN {\use:c{sd@#2#3}} #1 #2{#3}
66 }
67 \cs_set:Npn \math_sd_del_auxi:nN #1#2{ \math_delimiter>NNnNn #2 #1 }

```

Same for radicals.

```

68 \cs_set:Npn \math_sd_rad_aux:Nn #1#2{
69   \exp_args:Nf \math_sd_rad_auxi:n {\use:c{sd@#1#2}} #1 {#2}
70 }
71 \cs_set:Npn \math_sd_rad_auxi:n #1{ \math_radical:NnNn #1 }
72
73
74 % \cs_set:Npn \math_sd_aux:nn #1#2 {
75 %   \%exp_args:Nnf \use:nn { #1} { \math_sd_auxi:Nn #2 }
76 %   \exp_args:Nnf \use:nn { #1} { \use:c{sd@\use:nn#2} }
77 % }
78 % \cs_set:Npn \math_sd_auxi:Nn #1#2 {
79 %   \cs_if_free:cTF {sd@#1#2}
80 %   { #1{#2} }
81 %   { \use:c{sd@#1#2} }
82 %

```

compound symbols here

```

83 \cs_set_protected:Npn \math_bcsym_Ord:Nn #1#2 { \csmode { \mathord { \OrdSymbol {#2} } }%
84 \cs_set_protected:Npn \math_bcsym_Var:Nn #1#2 { \csmode { \mathord { \OrdSymbol {#2} } } }%
85 \cs_set_protected:Npn \math_bcsym_Bin:Nn #1#2 { \csmode { \mathbin { \OrdSymbol {#2} } } }%

```

```

86 \cs_set_protected:Npn \math_bcsym_Rel:Nn #1#2 { \@symtype \mathrel { \OrdSymbol {#2} } }%
87 \cs_set_protected:Npn \math_bcsym_Pun:Nn #1#2 { \@symtype \mathpunct { \OrdSymbol {#2} } }%
88 \cs_set_protected:Npn \math_bcsym_Coi:Nn #1#2 { \@symtype \mathop { \OrdSymbol {#2} } \intl{#1} }%
89 \cs_set_protected:Npn \math_bcsym_COs:Nn #1#2 { \@symtype \mathop { \OrdSymbol {#2} } \sum_{#1}^{#2} }%
90 \cs_set_protected:Npn \math_bcsym_Del:Nn #1#2 { \@symtype \mathopen { \OrdSymbol {#2} } }%
91 \cs_set_protected:Npn \math_bcsym_DeR:Nn #1#2 { \@symtype \mathclose { \OrdSymbol {#2} } }%
92 \cs_set_protected:Npn \math_bcsym_DeB:Nn #1#2 { \@symtype \mathord { \OrdSymbol {#2} } }%
93 \cs_set_protected:Npn \math_bcsym_DeA:Nn #1#2 { \@symtype \mathrel { \OrdSymbol {#2} } }%
94 \cs_set_protected:Npn \math_bcsym_Acc:Nn { \@symtype \mathrel { \OrdSymbol {#2} } } }% \@symAcc FIX!
95 % These three?
96 \cs_set_protected:Npn \math_bcsym_Ope:Nn #1#2 { \@symtype \mathopen { \OrdSymbol {#2} } } }% \@symVar
97 \cs_set_protected:Npn \math_bcsym_Clo:Nn #1#2 { \@symtype \mathclose { \OrdSymbol {#2} } } }% \@symVar
98 \cs_set_protected:Npn \math_bcsym_Inn:Nn #1#2 { \@symtype \mathinner { \OrdSymbol {#2} } } }% \@symVar
99
100 \let\@symtype\@firstofone
101 \let\sym@\global\global

```

The inline variants, using the basic operations. Currently we do not do anything to inline math.

```

102 \cs_new:Npn \math_isym_Ord:Nn { \math_bsym_Ord:Nn } }% \m@Ord
103 \cs_new:Npn \math_isym_Var:Nn { \math_bsym_Var:Nn } }% \m@Var
104 \cs_new:Npn \math_isym_Bin:Nn { \math_bsym_Bin:Nn } }% \m@Bin
105 \cs_new:Npn \math_isym_Rel:Nn { \math_bsym_Rel:Nn } }% \m@Bin
106 \cs_new:Npn \math_isym_Pun:Nn { \math_bsym_Pun:Nn } }% \m@Pun
107 \cs_new:Npn \math_isym_COs:Nn { \math_bsym_COs:Nn } }% \m@COS
108 \cs_new:Npn \math_isym_Coi:Nn { \math_bsym_Coi:Nn } }% \m@COI
109 \cs_new:Npn \math_isym_DeL:Nn { \math_bsym_DeL:Nn } }% \m@DeL
110 \cs_new:Npn \math_isym_DeR:Nn { \math_bsym_DeR:Nn } }% \m@DeR
111 \cs_new:Npn \math_isym_DeB:Nn { \math_bsym_DeB:Nn } }% \m@DeB
112 \cs_new:Npn \math_isym_DeA:Nn { \math_bsym_DeA:Nn } }% \m@DeA
113 \cs_new:Npn \math_isym_Rad:Nn { \math_bsym_Rad:Nn } }% \m@Rad
114 \cs_new:Npn \math_isym_Acc:Nn { \math_bsym_DeL:Nn } }% name is wrong
115 % inline compound
116 \cs_set_protected:Npn \math_icsym_Ord:Nn { \math_bcsym_Ord:Nn }
117 \cs_set_protected:Npn \math_icsym_Var:Nn { \math_bcsym_Var:Nn }
118 \cs_set_protected:Npn \math_icsym_Bin:Nn { \math_bcsym_Bin:Nn }
119 \cs_set_protected:Npn \math_icsym_Rel:Nn { \math_bcsym_Rel:Nn }
120 \cs_set_protected:Npn \math_icsym_Pun:Nn { \math_bcsym_Pun:Nn }
121 \cs_set_protected:Npn \math_icsym_Coi:Nn { \math_bcsym_Coi:Nn }
122 \cs_set_protected:Npn \math_icsym_COs:Nn { \math_bcsym_COs:Nn }
123 \cs_set_protected:Npn \math_icsym_DeL:Nn { \math_bcsym_DeL:Nn }
124 \cs_set_protected:Npn \math_icsym_DeR:Nn { \math_bcsym_DeR:Nn }
125 \cs_set_protected:Npn \math_icsym_DeB:Nn { \math_bcsym_DeB:Nn }
126 \cs_set_protected:Npn \math_icsym_DeA:Nn { \math_bcsym_DeA:Nn }
127 \cs_set_protected:Npn \math_icsym_Acc:Nn { \math_bcsym_Acc:Nn }
128 \cs_set_protected:Npn \math_icsym_Ope:Nn { \math_bcsym_Ope:Nn }
129 \cs_set_protected:Npn \math_icsym_Clo:Nn { \math_bcsym_Clo:Nn }
130 \cs_set_protected:Npn \math_icsym_Inn:Nn { \math_bcsym_Inn:Nn }

```

The display variants, using the basic operations. Currently we do not do

anything to inline math.

```

131 \cs_new:Npn \math_dsym_Ord:Nn { \math_bsym_Ord:Nn }
132 \cs_new:Npn \math_dsym_Var:Nn { \math_bsym_Var:Nn }
133 \cs_new:Npn \math_dsym_Bin:Nn { \math_bsym_Bin:Nn }
134 \cs_new:Npn \math_dsym_Rel:Nn { \math_bsym_Rel:Nn }
135 \cs_new:Npn \math_dsym_Pun:Nn { \math_bsym_Pun:Nn }
136 \cs_new:Npn \math_dsym_COs:Nn { \math_bsym_COs:Nn }
137 \cs_new:Npn \math_dsym_COi:Nn { \math_bsym_COi:Nn }
138 \cs_new:Npn \math_dsym_DeL:Nn { \math_bsym_DeL:Nn }
139 \cs_new:Npn \math_dsym_DeR:Nn { \math_bsym_DeR:Nn }
140 \cs_new:Npn \math_dsym_DeB:Nn { \math_bsym_DeB:Nn }
141 \cs_new:Npn \math_dsym_DeA:Nn { \math_bsym_DeA:Nn }
142 \cs_new:Npn \math_dsym_Rad:Nn { \math_bsym_Rad:Nn }
143 \cs_new:Npn \math_dsym_Acc:Nn { \math_bsym_Acc:Nn }
144 % inline compound
145 \cs_set_protected:Npn \math_dcsym_Ord:Nn { \math_bcsym_Ord:Nn }
146 \cs_set_protected:Npn \math_dcsym_Var:Nn { \math_bcsym_Var:Nn }
147 \cs_set_protected:Npn \math_dcsym_Bin:Nn { \math_bcsym_Bin:Nn }
148 \cs_set_protected:Npn \math_dcsym_Rel:Nn { \math_bcsym_Rel:Nn }
149 \cs_set_protected:Npn \math_dcsym_Pun:Nn { \math_bcsym_Pun:Nn }
150 \cs_set_protected:Npn \math_dcsym_COi:Nn { \math_bcsym_COi:Nn }
151 \cs_set_protected:Npn \math_dcsym_COs:Nn { \math_bcsym_COs:Nn }
152 \cs_set_protected:Npn \math_dcsym_DeL:Nn { \math_bcsym_DeL:Nn }
153 \cs_set_protected:Npn \math_dcsym_DeR:Nn { \math_bcsym_DeR:Nn }
154 \cs_set_protected:Npn \math_dcsym_DeB:Nn { \math_bcsym_DeB:Nn }
155 \cs_set_protected:Npn \math_dcsym_DeA:Nn { \math_bcsym_DeA:Nn }
156 \cs_set_protected:Npn \math_dcsym_Acc:Nn { \math_bcsym_Acc:Nn }
157 \cs_set_protected:Npn \math_dcsym_Ope:Nn { \math_bcsym_Ope:Nn }
158 \cs_set_protected:Npn \math_dcsym_Clo:Nn { \math_bcsym_Clo:Nn }
159 \cs_set_protected:Npn \math_dcsym_Inn:Nn { \math_bcsym_Inn:Nn }

```

Almost ready now! Now just need two commands to initialize these settings.

```

160 \cs_set:Npn \math_setup_inline_symbols:
161 {
162   \cs_set_eq:NN \math_sym_Ord:Nn \math_isym_Ord:Nn
163   \cs_set_eq:NN \math_sym_Var:Nn \math_isym_Var:Nn
164   \cs_set_eq:NN \math_sym_Bin:Nn \math_isym_Bin:Nn
165   \cs_set_eq:NN \math_sym_Rel:Nn \math_isym_Rel:Nn
166   \cs_set_eq:NN \math_sym_Pun:Nn \math_isym_Pun:Nn
167   \cs_set_eq:NN \math_sym_COs:Nn \math_isym_COs:Nn
168   \cs_set_eq:NN \math_sym_COi:Nn \math_isym_COi:Nn
169   \cs_set_eq:NN \math_sym_DeL:Nn \math_isym_DeL:Nn
170   \cs_set_eq:NN \math_sym_DeR:Nn \math_isym_DeR:Nn
171   \cs_set_eq:NN \math_sym_DeB:Nn \math_isym_DeB:Nn
172   \cs_set_eq:NN \math_sym_DeA:Nn \math_isym_DeA:Nn
173   \cs_set_eq:NN \math_sym_Rad:Nn \math_isym_Rad:Nn
174   \cs_set_eq:NN \math_sym_Acc:Nn \math_isym_Acc:Nn
175   \cs_set_eq:NN \math_csym_Ord:Nn \math_icsym_Ord:Nn
176   \cs_set_eq:NN \math_csym_Var:Nn \math_icsym_Var:Nn
177   \cs_set_eq:NN \math_csym_Bin:Nn \math_icsym_Bin:Nn

```

```

178 \cs_set_eq:NN \math_csym_Rel:Nn \math_icsym_Rel:Nn
179 \cs_set_eq:NN \math_csym_Pun:Nn \math_icsym_Pun:Nn
180 \cs_set_eq:NN \math_csym_COi:Nn \math_icsym_COi:Nn
181 \cs_set_eq:NN \math_csym_COs:Nn \math_icsym_COs:Nn
182 \cs_set_eq:NN \math_csym_DeL:Nn \math_icsym_DeL:Nn
183 \cs_set_eq:NN \math_csym_DeR:Nn \math_icsym_DeR:Nn
184 \cs_set_eq:NN \math_csym_DeB:Nn \math_icsym_DeB:Nn
185 \cs_set_eq:NN \math_csym_DeA:Nn \math_icsym_DeA:Nn
186 \cs_set_eq:NN \math_csym_Acc:Nn \math_icsym_Acc:Nn
187 \cs_set_eq:NN \math_csym_Ope:Nn \math_icsym_Ope:Nn
188 \cs_set_eq:NN \math_csym_Clo:Nn \math_icsym_Clo:Nn
189 \cs_set_eq:NN \math_csym_Inn:Nn \math_icsym_Inn:Nn
190 }
191
192 \cs_set:Npn \math_setup_display_symbols:
193 {
194   \cs_set_eq:NN \math_sym_Ord:Nn \math_dsym_Ord:Nn
195   \cs_set_eq:NN \math_sym_Var:Nn \math_dsym_Var:Nn
196   \cs_set_eq:NN \math_sym_Bin:Nn \math_dsym_Bin:Nn
197   \cs_set_eq:NN \math_sym_Rel:Nn \math_dsym_Rel:Nn
198   \cs_set_eq:NN \math_sym_Pun:Nn \math_dsym_Pun:Nn
199   \cs_set_eq:NN \math_sym_COs:Nn \math_dsym_COs:Nn
200   \cs_set_eq:NN \math_sym_COi:Nn \math_dsym_COi:Nn
201   \cs_set_eq:NN \math_sym_DeL:Nn \math_dsym_DeL:Nn
202   \cs_set_eq:NN \math_sym_DeR:Nn \math_dsym_DeR:Nn
203   \cs_set_eq:NN \math_sym_DeB:Nn \math_dsym_DeB:Nn
204   \cs_set_eq:NN \math_sym_DeA:Nn \math_dsym_DeA:Nn
205   \cs_set_eq:NN \math_sym_Rad:Nn \math_dsym_Rad:Nn
206   \cs_set_eq:NN \math_sym_Acc:Nn \math_dsym_DeL:Nn
207   \cs_set_eq:NN \math_csym_Ord:Nn \math_dcsym_Ord:Nn
208   \cs_set_eq:NN \math_csym_Var:Nn \math_dcsym_Var:Nn
209   \cs_set_eq:NN \math_csym_Bin:Nn \math_dcsym_Bin:Nn
210   \cs_set_eq:NN \math_csym_Rel:Nn \math_dcsym_Rel:Nn
211   \cs_set_eq:NN \math_csym_Pun:Nn \math_dcsym_Pun:Nn
212   \cs_set_eq:NN \math_csym_COi:Nn \math_dcsym_COi:Nn
213   \cs_set_eq:NN \math_csym_COs:Nn \math_dcsym_COs:Nn
214   \cs_set_eq:NN \math_csym_DeL:Nn \math_dcsym_DeL:Nn
215   \cs_set_eq:NN \math_csym_DeR:Nn \math_dcsym_DeR:Nn
216   \cs_set_eq:NN \math_csym_DeB:Nn \math_dcsym_DeB:Nn
217   \cs_set_eq:NN \math_csym_DeA:Nn \math_dcsym_DeA:Nn
218   \cs_set_eq:NN \math_csym_Acc:Nn \math_dcsym_Acc:Nn
219   \cs_set_eq:NN \math_csym_Ope:Nn \math_dcsym_Ope:Nn
220   \cs_set_eq:NN \math_csym_Clo:Nn \math_dcsym_Clo:Nn
221   \cs_set_eq:NN \math_csym_Inn:Nn \math_dcsym_Inn:Nn
222 }

```

Phew, that was it.

Well, almost. We need to set them up for use properly. Should they be added to `\everymath?` Probably, for math within displays. However, this is a lot of extra processing which we could tackle in the display setup.

```

223 \math_setup_inline_symbols:
      Need an active character for a second. Don't rely on ~ being active!
224 \edef\tmp{\catcode\z@=\the\catcode\z@}
225 \catcode\z@=\active
226 \def\DeclareFlexSymbol#1#2#3#4{%
227   \begingroup
228   \cs_set_protected:Npx\@tempb{
229     \exp_not:N\@sym\exp_not:N#1\exp_not:c{math_sym_#2:Nn}%
230     \exp_not:c{mg@#3}{#4}%
231   }
232   \ifcat\exp_not:N#1\relax
233     \sym@global\let#1\@tempb
234   \else
235     \sym@global\mathcode`#1="8000\relax
236     \lccode\z@='#1\relax
237     \lowercase{\sym@global\let^{\@tempb}}% zero char
238   \fi
239   \endgroup
240 }
241 \tmp % restore catcode
242 \cs_set:Npn \DeclareFlexDelimiter #1#2#3#4#5#6{%
243   \DeclareFlexSymbol{#1}{#2}{#3}{#4}%
244   \cs_gset:cp{sd@\use:c{mg@#3}{#4}}{\exp_not:c{mg@#5}{#6}}%
245 }
246
\DeclareFlexCompoundSymbol{\cdots}{Inn}{\cdotp\cdotp\cdotp} \def\@symInn#1#2{\@syntyp
\@syntype \mathinner{\OrdSymbol{\cdotp\cdotp\cdotp}}}
247 \def\DeclareFlexCompoundSymbol#1#2#3{%
248   \exp_args:NNo \DeclareRobustCommand#1{\csname math_csym_#2:Nn\endcsname#1{#3}}%
249   \sym@global\let#1\relax
250 }
251 \DeclareRobustCommand{textchar}{\text@char{textfont}}
252 \DeclareRobustCommand{scriptchar}{\text@char{scriptfont}}%
Simplified the next bit because now the slot is read as one argument so no afterassignment and what have you. Just drop the char directly.
253 \def{text@char@sym#1#2#3#4}{% #3=fam, #4=slot
254   \begingroup
255     \cs_set_eq:NN \prg_do_nothing: % defense against infinite loops
the next line will result in \scriptfont<num>, where #3 provides the <num>.
256     \the{text@script@char#3}%
257     \char"#4\endgroup
258 }
259 \edef\tmp{\catcode\z@=\the\catcode\z@}
260 \catcode\z@=\active
261 \def{text@char#1#2}{\begingroup
262   \check@mathfonts
263   \cs_set_eq:NN \text@script@char #1

```

```

264 \cs_set_eq:NN \csmode \text@char@csmode
265 \cs_set_eq:NN \csmode@type \use_i:nn
266 \cs_set_eq:NN \OrdSymbol \use:n
267 \cs_set_eq:NN \ifmmode \iftrue
268 \everymath{\use:none:n}%
269 \def\mkern{\muskip{z@}}
270 \cs_set_eq:NN \mskip \mkern
271 \ifcat\relax\noexpand#2% true if #2 is a cs.
272   #2%
273 \else
274   \lccode{z@=\expandafter`\string#2\relax
275   \lowercase{`^`@}}%
276 \fi
277 \endgroup
278 }
279 \tmp % restore catcode
280 \providecommand\textprime{%
281 \DeclRobustCommand\textprime{\leavevmode
282   \raise.8ex\hbox{\text@char\scriptfont\prime}}%
283 }
284 \@ifundefined{resetMathstrut@}{}{%
285   \def\resetMathstrut@{%
286     \setbox{z@}\hbox{\textchar\vert}%
287     \ht{\Mathstrutbox@\ht{z@}\dp{\Mathstrutbox@\dp{z@}}%
288   }%
289 }
Arrow fills. changed to 7mu as in amsmath
290 \ifundefined{rightarrowfill@}{}{%
291   \def\rightarrowfill@{\m@th\setbox{h{\relbar}}\ht{z@}\z@%
292   \#1\copy{z@\mkern-7mu\cleaders
293   \hbox{\#1\mkern-2mu\box{z@\mkern-2mu}}\hfill
294   \mkern-6mu\OrdSymbol{\rightarrow}}$}
295 \def\leftarrowfill@{\m@th\setbox{h{\relbar}}\ht{z@}\z@%
296   \#1\OrdSymbol{\leftarrow}\mkern-6mu\cleaders
297   \hbox{\#1\mkern-2mu\copy{z@\mkern-2mu}}\hfill
298   \mkern-7mu\box{z@$}}
299 \def\leftrightarrowfill@{\m@th\setbox{h{\relbar}}\ht{z@}\z@%
300   \#1\OrdSymbol{\leftarrow}\mkern-6mu\cleaders
301   \hbox{\#1\mkern-2mu\box{z@\mkern-2mu}}\hfill
302   \mkern-6mu\OrdSymbol{\rightarrow}}$}
303 }
hey, this looks like a simple case switch...
304 \def\binrel@sym#1#2#3#4{%
305   \xdef\binrel@{\#1{%
306     \ifx\math_sym_Ord:Nn #2 \math_csym_Ord:Nn
307     \else\ifx\math_sym_Var:Nn#2 \math_csym_Var:Nn
308     \else\ifx\math_sym_COs:Nn#2 \math_csym_COs:Nn
309     \else\ifx\math_sym_COi:Nn#2 \math_csym_COi:Nn
310     \else\ifx\math_sym_Bin:Nn#2 \math_csym_Bin:Nn

```

```

311     \else\ifx\math_sym_Rel:Nn#2 \math_csym_Rel:Nn
312     \else\ifx\math_sym_Pun:Nn#2 \math_csym_Pun:Nn
313     \else\exp_not:N\@symErr \fi\fi\fi\fi\fi\fi
314     ?{\exp_not:N\OrdSymbol{##1}}}%
315 }
316
317 \def\binrel@a{%
318   \def\math_sym_Ord:Nn##1##2{\gdef\binrel@@####1{\math_sym_Ord:Nn##1{\OrdSymbol{####1}}}}%
319   \def\math_sym_Var:Nn##1##2{\gdef\binrel@@####1{\math_sym_Var:Nn##1{\OrdSymbol{####1}}}}%
320   \def\math_sym_COs:Nn##1##2{\gdef\binrel@@####1{\math_sym_COs:Nn##1{\OrdSymbol{####1}}}}%
321   \def\math_sym_COi:Nn##1##2{\gdef\binrel@@####1{\math_sym_COi:Nn##1{\OrdSymbol{####1}}}}%
322   \def\math_sym_Bin:Nn##1##2{\gdef\binrel@@####1{\math_sym_Bin:Nn##1{\OrdSymbol{####1}}}}%
323   \def\math_sym_Rel:Nn##1##2{\gdef\binrel@@####1{\math_sym_Rel:Nn##1{\OrdSymbol{####1}}}}%
324   \def\math_sym_Pun:Nn##1##2{\gdef\binrel@@####1{\math_sym_Pun:Nn##1{\OrdSymbol{####1}}}}}%
325 }
326 \def\binrel@#1{%
327   \setbox\z@\hbox{$%
328     \let\mathchoice@gobblethree
329     \let\@sym\binrel@sym \binrel@a
330     #1$}%
331 }
332 \def\@symextension{sym}
333 \newcommand\usesymbols[1]{%
334   \clist_map_variable:nNn{#1}\@tempb{%
335     \exp_args:No\@onefilewithoptions{\@tempb}[] []\@symextension
336   }%
337 }
338 % Need to introduce \ProvidesExplFile somehow
339 \newcommand\ProvidesSymbols[1]{\ProvidesFile{#1.sym}}
340 \DeclareRobustCommand{\not}[1]{\math_csym_Rel:Nn\not{\OrdSymbol{\notRel#1}}}
341 \DeclareRobustCommand{\OrdSymbol}[1]{%
342   \begingroup\mathchars@reset#1\endgroup
343 }
344 \def\mathchars@reset{\let\@sym\@sym@ord \let\@symtype\@symtype@ord
345   \let\OrdSymbol\relax}
346 \def\@symtype@ord#1{}% a strange sort of \@gobble
347 \def\@sym@ord#1#2{\exp_after:wN\@sym@ord@a\string#2@nil}%
348 \begingroup
349 \lccode`\.=`\_
350 \lowercase{\endgroup
351 \def\@sym@ord@a#1.#2.}{#3#4@nil#5#6}%
352 \if D#3
353   \%math_ord_delim_aux:Nn #5{#6}

```

```

353     \math_sd_del_aux:Nnn 0 #5{#6}%
354     \else
355     \math_char:NNn 0 #5{#6}
356     \fi
357 }
358 \cs_set:Nn \math_ord_delim_aux:Nn {
359   \math_sd_aux:nn { \math_char:NNn 0 } {#1{#2}}
360 }

```

Before declaring any math characters active, we have to take care of a small problem with `amsmath v2.x`, if it is loaded before `flexisym`. `\std@minus` and `\std@equal` are defined as

```

\mathchardef\std@minus\mathcode`-\relax
\mathchardef\std@equal\mathcode`=\relax

```

in `amsmath.sty` and again `\AtBeginDocument`. The latter is because

In case some alternative math fonts are loaded later. [`amsmath.dtx`]

The problem arises because `flexisym` sets the mathcode of all symbols to 32768 which is illegal for a `\mathchardef`.

We have to remove the assignments from the `\AtBeginDocument` hook as they will cause an error there.

```

361 \@ifpackageloaded{amsmath}{%
362   \begingroup

```

Split the contents of `\@begindocumenthook` by reading what we search for as a delimited argument and ensure these two assignments do not take place. It is questionable if anything reasonable can be done to them. In the case of a package such as `mathpazo` which defines

```
\DeclareMathSymbol{=}{\mathrel}{upright}{3D}
```

the `\Relbar` will look wrong if we don't use the correct symbol. The way to solve this is define additional `.sym` files which contain the definition of `\relbar` and `\Relbar` needed. We need those additional files anyway for things like `\joinord`.

```

363   \long\def\next{\mathchardef\std@minus\mathcode`-\relax
364             \mathchardef\std@equal\mathcode`=\relax\#2\flexi@stop{%
365   \toks0{#1#2}%
366   \xdef\@begindocumenthook{\the\toks0}%
367 }%
368 \expandafter\next\@begindocumenthook\flexi@stop
369 \endgroup
370 }{}}

```

There is problem when using `\DeclareMathOperator` as the operators defined call a command `\newmcodes@` which relies on the mathcode of `-` being less than 32768. We delay the definition `\AtBeginDocument` in case `amssymb` hasn't been loaded yet.

```

371 \AtBeginDocument{%
372 \def\newmcodes@{%
373   \mathcode `\'39\space
374   \mathcode `'*42\space
375   \mathcode `.\"613A\space
376   \ifnum\mathcode`-=45\space
377   \else

```

The extra check. Don't do anything if - is math active.

```

378   \ifnum\mathcode`-=32768\space
379   \else
380     \mathchardef \std@minus \mathcode `-\relax
381   \fi
382 \fi
383 \mathcode `-\45\space
384 \mathcode `/47\space
385 \mathcode `\:603A\space\relax
386 }%
387 }

```

And we then continue with the options.

```

388 \DeclareOption{mathstyleoff}{%
389   \PassOptionsToPackage{noactivechars}{mathstyle}}
390 \DeclareOption{cmbase}{\usesymbols{cmbase}}
391 \DeclareOption{mathpazo}{\usesymbols{mathpazo}}
392 \DeclareOption{mathptmx}{\usesymbols{mathptmx}}
393 \ExecuteOptions{cmbase}
394 \ProcessOptions\relax
395 \renewcommand{\lnot}{\neg}
396 \renewcommand{\land}{\wedge}
397 \renewcommand{\lor}{\vee}
398 \renewcommand{\le}{\leq}
399 \renewcommand{\ge}{\geq}
400 \renewcommand{\ne}{\neq}
401 \renewcommand{\owns}{\ni}
402 \renewcommand{\gets}{\leftarrow}
403 \renewcommand{\to}{\rightarrow}
404 \renewcommand{\|}{\Vert}
405 \RequirePackage{mathstyle}
406 </package>\endinput

```

## 2 cmbase, mathpazo, mathptmx

For each math font package we define a corresponding symbol file with extension `sym`. The Computer Modern base is called `cmbase` and `mathpazo` and `mathptmx` corresponds to the packages. The definitions are almost identical as they mostly concern the positions in the math font encodings. Look for differences in `\joinord`, `\relbar` and `\Relbar`. If you inspect the source code, you'll see that the support

for `mathptmx` didn't require any work but I thought it better to create a `sym` file to maintain a uniform interface.

**Open question on ! and ?: maybe they should have type 'Pun' instead of 'DeR'. Need to search for uses in math in AMS archives. Or, maybe add a special 'Clo' type for them: non-extensible closing delimiter.**

Default mathgroup setup.

```

407 {*cmbase | mathpazo | mathptmx}
408 {cmbase} \ProvidesSymbols{cmbase}[2007/12/19 v0.92]
409 {mathpazo} \ProvidesSymbols{mathpazo}[2010/07/11 v0.3]
410 {mathptmx} \ProvidesSymbols{mathptmx}[2010/07/11 v0.3]
411 \ExplSyntaxOn
412 \cs_gset:cpx {mg@OT1} {\hexnumber@\symoperators}
413 \cs_gset:cpx {mg@OML} {\hexnumber@\symletters}
414 \cs_gset:cpx {mg@OMS} {\hexnumber@\symsymbols}
415 \cs_gset:cpx {mg@OMX} {\hexnumber@\symlargesymbols}
416 \cs_gset:Npx \mg@bin {\mg@OMS}
417 \cs_gset:Npx \mg@del {\mg@OMX}
418 \cs_gset:Npx \mg@digit {\exp_not:c{mg@OT1}}
419 \cs_gset:Npn \mg@latin {\mg@OML}
420 \cs_gset_eq:NN \mg@Latin \mg@latin
421 \cs_gset_eq:NN \mg@greek \mg@latin
422 {cmbase | mathptmx} \cs_gset_eq:NN\mg@Greek\mg@digit

```

Mathpazo takes the upper case greeks from the letter font if `slantedGreek` is in effect, but from `upright` if not. Mathptmx also takes the slanted greek from the letter font.

```

423 {mathpazo} \@ifpackagewith{mathpazo}{slantedGreek}{%
424 {mathpazo} \cs_gset_eq:NN\mg@Greek\mg@latin
425 {mathpazo}}{%
426 {mathpazo} \cs_gset:cpx{\mg@Greek}{\hexnumber@\symupright}
427 {mathpazo}}%
428 {mathptmx} \@ifpackagewith{mathptmx}{slantedGreek}{%
429 {mathptmx} \cs_gset_eq:NN\mg@Greek\mg@latin
430 {mathptmx}}{%
431 \cs_gset_eq:NN \mg@rel \mg@bin
432 \cs_gset_eq:NN \mg@ord \mg@bin
433 \cs_gset_eq:NN \mg@cop \mg@del

```

Symbols from the 128-character `cmr` encoding. Paren and square bracket delimiters from this encoding are covered by the definitions in the `cme` section, however.

```

434 \DeclareFlexSymbol{!} {Pun}{OT1}{21}
435 \DeclareFlexSymbol{+} {Bin}{OT1}{2B}
436 \DeclareFlexSymbol{:} {Rel}{OT1}{3A}
437 \DeclareFlexSymbol{\colon}{Pun}{OT1}{3A}
438 \DeclareFlexSymbol{;} {Pun}{OT1}{3B}
439 \DeclareFlexSymbol{=} {Rel}{OT1}{3D}

```

```
440 \DeclareFlexSymbol{?} {Pun}{OT1}{3F}
```

*AMSTEX*, and therefore the `amsmath` package, make the uppercase Greek letters class 0 (nonvariable) instead of 7 (variable), to eliminate the glaring inconsistency with lowercase Greek. (In plain *TeX*, `\bf\Delta` works, while `\bf\delta` doesn't.) Let us try to make them both variable (fonts permitting) instead of nonvariable.

```
441 \DeclareFlexSymbol{\Gamma} {Var}{Greek}{00}
442 \DeclareFlexSymbol{\Delta} {Var}{Greek}{01}
443 \DeclareFlexSymbol{\Theta} {Var}{Greek}{02}
444 \DeclareFlexSymbol{\Lambda} {Var}{Greek}{03}
445 \DeclareFlexSymbol{\Xi} {Var}{Greek}{04}
446 \DeclareFlexSymbol{\Pi} {Var}{Greek}{05}
447 \DeclareFlexSymbol{\Sigma} {Var}{Greek}{06}
448 \DeclareFlexSymbol{\Upsilon} {Var}{Greek}{07}
449 \DeclareFlexSymbol{\Phi} {Var}{Greek}{08}
450 \DeclareFlexSymbol{\Psi} {Var}{Greek}{09}
451 \DeclareFlexSymbol{\Omega} {Var}{Greek}{0A}
```

Decimal digits.

```
452 \DeclareFlexSymbol{0}{Var}{digit}{30}
453 \DeclareFlexSymbol{1}{Var}{digit}{31}
454 \DeclareFlexSymbol{2}{Var}{digit}{32}
455 \DeclareFlexSymbol{3}{Var}{digit}{33}
456 \DeclareFlexSymbol{4}{Var}{digit}{34}
457 \DeclareFlexSymbol{5}{Var}{digit}{35}
458 \DeclareFlexSymbol{6}{Var}{digit}{36}
459 \DeclareFlexSymbol{7}{Var}{digit}{37}
460 \DeclareFlexSymbol{8}{Var}{digit}{38}
461 \DeclareFlexSymbol{9}{Var}{digit}{39}
```

Symbols from the 128-character `cmmi` encoding.

```
462 \DeclareFlexSymbol{,}{Pun}{OML}{3B}
463 \DeclareFlexSymbol{.}{Ord}{OML}{3A}
464 \DeclareFlexSymbol{/}{Ord}{OML}{3D}
465 \DeclareFlexSymbol{<}{Rel}{OML}{3C}
466 \DeclareFlexSymbol{>}{Rel}{OML}{3E}
```

To do: make the Var property of lc Greek work properly.

```
467 \DeclareFlexSymbol{\alpha} {Var}{greek}{0B}
468 \DeclareFlexSymbol{\beta} {Var}{greek}{0C}
469 \DeclareFlexSymbol{\gamma} {Var}{greek}{0D}
470 \DeclareFlexSymbol{\delta} {Var}{greek}{0E}
471 \DeclareFlexSymbol{\epsilon} {Var}{greek}{0F}
472 \DeclareFlexSymbol{\zeta} {Var}{greek}{10}
473 \DeclareFlexSymbol{\eta} {Var}{greek}{11}
474 \DeclareFlexSymbol{\theta} {Var}{greek}{12}
475 \DeclareFlexSymbol{\iota} {Var}{greek}{13}
476 \DeclareFlexSymbol{\kappa} {Var}{greek}{14}
477 \DeclareFlexSymbol{\lambda} {Var}{greek}{15}
478 \DeclareFlexSymbol{\mu} {Var}{greek}{16}
```

```

479 \DeclareFlexSymbol{\nu}           {Var}{greek}{17}
480 \DeclareFlexSymbol{\xi}           {Var}{greek}{18}
481 \DeclareFlexSymbol{\pi}           {Var}{greek}{19}
482 \DeclareFlexSymbol{\rho}           {Var}{greek}{1A}
483 \DeclareFlexSymbol{\sigma}          {Var}{greek}{1B}
484 \DeclareFlexSymbol{\tau}           {Var}{greek}{1C}
485 \DeclareFlexSymbol{\upsilon}         {Var}{greek}{1D}
486 \DeclareFlexSymbol{\phi}           {Var}{greek}{1E}
487 \DeclareFlexSymbol{\chi}           {Var}{greek}{1F}
488 \DeclareFlexSymbol{\psi}           {Var}{greek}{20}
489 \DeclareFlexSymbol{\omega}          {Var}{greek}{21}
490 \DeclareFlexSymbol{\varepsilon}        {Var}{greek}{22}
491 \DeclareFlexSymbol{\vartheta}        {Var}{greek}{23}
492 \DeclareFlexSymbol{\varpi}           {Var}{greek}{24}
493 \DeclareFlexSymbol{\varrho}           {Var}{greek}{25}
494 \DeclareFlexSymbol{\varsigma}         {Var}{greek}{26}
495 \DeclareFlexSymbol{\varphi}          {Var}{greek}{27}

```

Note that in plain TeX \imath and \jmath are not variable-font. But if a j changes font to, let's say, sans serif or calligraphic, a dotless j in the same context should change font in the same way.

```

496 \DeclareFlexSymbol{\imath}          {Var}{OML}{7B}
497 \DeclareFlexSymbol{\jmath}           {Var}{OML}{7C}
498 \DeclareFlexSymbol{\ell}            {Ord}{OML}{60}
499 \DeclareFlexSymbol{\wp}             {Ord}{OML}{7D}
500 \DeclareFlexSymbol{\partial}         {Ord}{OML}{40}
501 \DeclareFlexSymbol{\flat}           {Ord}{OML}{5B}
502 \DeclareFlexSymbol{\natural}        {Ord}{OML}{5C}
503 \DeclareFlexSymbol{\sharp}           {Ord}{OML}{5D}
504 \DeclareFlexSymbol{\triangleleft}      {Bin}{OML}{2F}
505 \DeclareFlexSymbol{\triangleright}     {Bin}{OML}{2E}
506 \DeclareFlexSymbol{\star}            {Bin}{OML}{3F}
507 \DeclareFlexSymbol{\smile}           {Rel}{OML}{5E}
508 \DeclareFlexSymbol{\frown}           {Rel}{OML}{5F}
509 \DeclareFlexSymbol{\leftharpoonup}     {Rel}{OML}{28}
510 \DeclareFlexSymbol{\leftharpoondown}   {Rel}{OML}{29}
511 \DeclareFlexSymbol{\rightharpoonup}    {Rel}{OML}{2A}
512 \DeclareFlexSymbol{\rightharpoondown}  {Rel}{OML}{2B}

```

#### Latin

```

513 \DeclareFlexSymbol{a}{Var}{latin}{61}
514 \DeclareFlexSymbol{b}{Var}{latin}{62}
515 \DeclareFlexSymbol{c}{Var}{latin}{63}
516 \DeclareFlexSymbol{d}{Var}{latin}{64}
517 \DeclareFlexSymbol{e}{Var}{latin}{65}
518 \DeclareFlexSymbol{f}{Var}{latin}{66}
519 \DeclareFlexSymbol{g}{Var}{latin}{67}
520 \DeclareFlexSymbol{h}{Var}{latin}{68}
521 \DeclareFlexSymbol{i}{Var}{latin}{69}
522 \DeclareFlexSymbol{j}{Var}{latin}{6A}

```

```

523 \DeclareFlexSymbol{k}{Var}{latin}{6B}
524 \DeclareFlexSymbol{l}{Var}{latin}{6C}
525 \DeclareFlexSymbol{m}{Var}{latin}{6D}
526 \DeclareFlexSymbol{n}{Var}{latin}{6E}
527 \DeclareFlexSymbol{o}{Var}{latin}{6F}
528 \DeclareFlexSymbol{p}{Var}{latin}{70}
529 \DeclareFlexSymbol{q}{Var}{latin}{71}
530 \DeclareFlexSymbol{r}{Var}{latin}{72}
531 \DeclareFlexSymbol{s}{Var}{latin}{73}
532 \DeclareFlexSymbol{t}{Var}{latin}{74}
533 \DeclareFlexSymbol{u}{Var}{latin}{75}
534 \DeclareFlexSymbol{v}{Var}{latin}{76}
535 \DeclareFlexSymbol{w}{Var}{latin}{77}
536 \DeclareFlexSymbol{x}{Var}{latin}{78}
537 \DeclareFlexSymbol{y}{Var}{latin}{79}
538 \DeclareFlexSymbol{z}{Var}{latin}{7A}
539 \DeclareFlexSymbol{A}{Var}{Latin}{41}
540 \DeclareFlexSymbol{B}{Var}{Latin}{42}
541 \DeclareFlexSymbol{C}{Var}{Latin}{43}
542 \DeclareFlexSymbol{D}{Var}{Latin}{44}
543 \DeclareFlexSymbol{E}{Var}{Latin}{45}
544 \DeclareFlexSymbol{F}{Var}{Latin}{46}
545 \DeclareFlexSymbol{G}{Var}{Latin}{47}
546 \DeclareFlexSymbol{H}{Var}{Latin}{48}
547 \DeclareFlexSymbol{I}{Var}{Latin}{49}
548 \DeclareFlexSymbol{J}{Var}{Latin}{4A}
549 \DeclareFlexSymbol{K}{Var}{Latin}{4B}
550 \DeclareFlexSymbol{L}{Var}{Latin}{4C}
551 \DeclareFlexSymbol{M}{Var}{Latin}{4D}
552 \DeclareFlexSymbol{N}{Var}{Latin}{4E}
553 \DeclareFlexSymbol{O}{Var}{Latin}{4F}
554 \DeclareFlexSymbol{P}{Var}{Latin}{50}
555 \DeclareFlexSymbol{Q}{Var}{Latin}{51}
556 \DeclareFlexSymbol{R}{Var}{Latin}{52}
557 \DeclareFlexSymbol{S}{Var}{Latin}{53}
558 \DeclareFlexSymbol{T}{Var}{Latin}{54}
559 \DeclareFlexSymbol{U}{Var}{Latin}{55}
560 \DeclareFlexSymbol{V}{Var}{Latin}{56}
561 \DeclareFlexSymbol{W}{Var}{Latin}{57}
562 \DeclareFlexSymbol{X}{Var}{Latin}{58}
563 \DeclareFlexSymbol{Y}{Var}{Latin}{59}
564 \DeclareFlexSymbol{Z}{Var}{Latin}{5A}

```

The \ldotpPun glyph is used in constructing the \ldots symbol. It is just a period with a different math symbol class. \lhookRel and \rhookRel are used in a similar way for building hooked arrow symbols.

```

565 \DeclareFlexSymbol{\ldotpPun}{Pun}{OML}{3A}
566 \def\ldotpPun{
567 \DeclareFlexSymbol{\lhookRel}{Rel}{OML}{2C}
568 \DeclareFlexSymbol{\rhookRel}{Rel}{OML}{2D}

```

Symbols from the 128-character cmsy encoding.

```
569 \DeclareFlexSymbol{*}          {Bin}{bin}{03} % \ast
570 \DeclareFlexSymbol{-}          {Bin}{bin}{00}
571 \DeclareFlexSymbol{|}          {Ord}{OMS}{6A}
572 \DeclareFlexSymbol{\aleph}      {Ord}{ord}{40}
573 \DeclareFlexSymbol{\Re}         {Ord}{ord}{3C}
574 \DeclareFlexSymbol{\Im}         {Ord}{ord}{3D}
575 \DeclareFlexSymbol{\infty}      {Ord}{ord}{31}
576 \DeclareFlexSymbol{\prime}      {Ord}{ord}{30}
577 \DeclareFlexSymbol{\emptyset}    {Ord}{ord}{3B}
578 \DeclareFlexSymbol{\nabla}       {Ord}{ord}{72}
579 \DeclareFlexSymbol{\top}        {Ord}{ord}{3E}
580 \DeclareFlexSymbol{\bot}        {Ord}{ord}{3F}
581 \DeclareFlexSymbol{\triangle}   {Ord}{ord}{34}
582 \DeclareFlexSymbol{\forall}     {Ord}{ord}{38}
583 \DeclareFlexSymbol{\exists}     {Ord}{ord}{39}
584 \DeclareFlexSymbol{\neg}        {Ord}{ord}{3A}
585 \DeclareFlexSymbol{\clubsuit}   {Ord}{ord}{7C}
586 \DeclareFlexSymbol{\diamondsuit} {Ord}{ord}{7D}
587 \DeclareFlexSymbol{\heartsuit}  {Ord}{ord}{7E}
588 \DeclareFlexSymbol{\spadesuit}  {Ord}{ord}{7F}
589 \DeclareFlexSymbol{\smallint}    {C0s}{OMS}{73}
```

Binary operators.

```
590 \DeclareFlexSymbol{\bigtriangleup} {Bin}{bin}{34}
591 \DeclareFlexSymbol{\bigtriangledown} {Bin}{bin}{35}
592 \DeclareFlexSymbol{\wedge}          {Bin}{bin}{5E}
593 \DeclareFlexSymbol{\vee}           {Bin}{bin}{5F}
594 \DeclareFlexSymbol{\cap}          {Bin}{bin}{5C}
595 \DeclareFlexSymbol{\cup}           {Bin}{bin}{5B}
596 \DeclareFlexSymbol{\ddagger}       {Bin}{bin}{7A}
597 \DeclareFlexSymbol{\dagger}        {Bin}{bin}{79}
598 \DeclareFlexSymbol{\sqcap}         {Bin}{bin}{75}
599 \DeclareFlexSymbol{\sqcup}         {Bin}{bin}{74}
600 \DeclareFlexSymbol{\uplus}         {Bin}{bin}{5D}
601 \DeclareFlexSymbol{\amalg}         {Bin}{bin}{71}
602 \DeclareFlexSymbol{\diamond}       {Bin}{bin}{05}
603 \DeclareFlexSymbol{\bullet}        {Bin}{bin}{0F}
604 \DeclareFlexSymbol{\wr}            {Bin}{bin}{6F}
605 \DeclareFlexSymbol{\div}           {Bin}{bin}{04}
606 \DeclareFlexSymbol{\odot}          {Bin}{bin}{0C}
607 \DeclareFlexSymbol{\oslash}         {Bin}{bin}{0B}
608 \DeclareFlexSymbol{\otimes}         {Bin}{bin}{0A}
609 \DeclareFlexSymbol{\ominus}         {Bin}{bin}{09}
610 \DeclareFlexSymbol{\oplus}          {Bin}{bin}{08}
611 \DeclareFlexSymbol{\mp}             {Bin}{bin}{07}
612 \DeclareFlexSymbol{\pm}             {Bin}{bin}{06}
613 \DeclareFlexSymbol{\circ}           {Bin}{bin}{0E}
614 \DeclareFlexSymbol{\bigcirc}         {Bin}{bin}{0D}
615 \DeclareFlexSymbol{\setminus}        {Bin}{bin}{6E}
```

```

616 \DeclareFlexSymbol{\cdot} {Bin}{bin}{01}
617 \DeclareFlexSymbol{\ast} {Bin}{bin}{03}
618 \DeclareFlexSymbol{\times} {Bin}{bin}{02}

Relation symbols.

619 \DeclareFlexSymbol{\propto} {Rel}{rel}{2F}
620 \DeclareFlexSymbol{\sqsubseteq} {Rel}{rel}{76}
621 \DeclareFlexSymbol{\sqsupseteq} {Rel}{rel}{77}
622 \DeclareFlexSymbol{\parallel} {Rel}{rel}{6B}
623 \DeclareFlexSymbol{\mid} {Rel}{rel}{6A}
624 \DeclareFlexSymbol{\dashv} {Rel}{rel}{61}
625 \DeclareFlexSymbol{\vdash} {Rel}{rel}{60}
626 \DeclareFlexSymbol{\nearrow} {Rel}{rel}{25}
627 \DeclareFlexSymbol{\searrow} {Rel}{rel}{26}
628 \DeclareFlexSymbol{\nwarrow} {Rel}{rel}{2D}
629 \DeclareFlexSymbol{\swarrow} {Rel}{rel}{2E}
630 \DeclareFlexSymbol{\Leftrightarrow}{Rel}{rel}{2C}
631 \DeclareFlexSymbol{\Leftarrow} {Rel}{rel}{28}
632 \DeclareFlexSymbol{\Rightarrow} {Rel}{rel}{29}
633 \DeclareFlexSymbol{\leq} {Rel}{rel}{14}
634 \DeclareFlexSymbol{\geq} {Rel}{rel}{15}
635 \DeclareFlexSymbol{\succ} {Rel}{rel}{1F}
636 \DeclareFlexSymbol{\prec} {Rel}{rel}{1E}
637 \DeclareFlexSymbol{\approx} {Rel}{rel}{19}
638 \DeclareFlexSymbol{\succeq} {Rel}{rel}{17}
639 \DeclareFlexSymbol{\preceq} {Rel}{rel}{16}
640 \DeclareFlexSymbol{\supset} {Rel}{rel}{1B}
641 \DeclareFlexSymbol{\subset} {Rel}{rel}{1A}
642 \DeclareFlexSymbol{\supseteq} {Rel}{rel}{13}
643 \DeclareFlexSymbol{\subseteq} {Rel}{rel}{12}
644 \DeclareFlexSymbol{\in} {Rel}{rel}{32}
645 \DeclareFlexSymbol{\ni} {Rel}{rel}{33}
646 \DeclareFlexSymbol{\gg} {Rel}{rel}{1D}
647 \DeclareFlexSymbol{\ll} {Rel}{rel}{1C}
648 \DeclareFlexSymbol{\Leftrightarrow}{Rel}{rel}{24}
649 \DeclareFlexSymbol{\Leftarrow} {Rel}{rel}{20}
650 \DeclareFlexSymbol{\Rightarrow} {Rel}{rel}{21}
651 \DeclareFlexSymbol{\sim} {Rel}{rel}{18}
652 \DeclareFlexSymbol{\simeq} {Rel}{rel}{27}
653 \DeclareFlexSymbol{\perp} {Rel}{rel}{3F}
654 \DeclareFlexSymbol{\equiv} {Rel}{rel}{11}
655 \DeclareFlexSymbol{\asymp} {Rel}{rel}{10}

```

The `\notRel` glyph is a special zero-width glyph intended only for use in constructing negated symbols. `\mapstoRel` and `\cdotpUn` have similar but more restricted applications.

```

656 \DeclareFlexSymbol{\notRel} {Rel}{rel}{36}
657 \DeclareFlexSymbol{\mapstoOrd}{Ord}{OMS}{37}
658 \DeclareFlexSymbol{\cdotpOrd} {Ord}{OMS}{01}
659 \cs_set:Npn\cdotpUn{\mathpunct{\cdotpOrd}}

```

Symbols from the 128-character `cmex` encoding. `C0s` stands for ‘cumulative operator (sum-like)’. `C0i` stands for ‘cumulative operator (integral-like)’. These typically differ only in the default placement of limits. `cop` stands for ‘cumulative operator math group’.

```

660 \DeclareFlexSymbol{\coprod}  {C0s}{cop}{60}
661 \DeclareFlexSymbol{\bigvee}    {C0s}{cop}{57}
662 \DeclareFlexSymbol{\bigwedge}  {C0s}{cop}{56}
663 \DeclareFlexSymbol{\biguplus}  {C0s}{cop}{55}
664 \DeclareFlexSymbol{\bigcap}   {C0s}{cop}{54}
665 \DeclareFlexSymbol{\bigcup}   {C0s}{cop}{53}
666 \DeclareFlexSymbol{\int}     {C0i}{cop}{52}
667 \DeclareFlexSymbol{\prod}    {C0s}{cop}{51}
668 \DeclareFlexSymbol{\sum}    {C0s}{cop}{50}
669 \DeclareFlexSymbol{\bigotimes}{C0s}{cop}{4E}
670 \DeclareFlexSymbol{\bigoplus} {C0s}{cop}{4C}
671 \DeclareFlexSymbol{\bigodot}  {C0s}{cop}{4A}
672 \DeclareFlexSymbol{\oint}    {C0i}{cop}{48}
673 \DeclareFlexSymbol{\bigsqcup} {C0s}{cop}{46}

```

Delimiter symbols. `DeL` stands for ‘delimiter (left)’. `DeR` stands for ‘delimiter (right)’. `DeB` stands for ‘delimiter (bidirectional)’. The principal encoding point for an extensible delimiter is the first link in the list of linked sizes as specified in the font metric information. For a math encoding such as OT1/OML/OMS/OMX where not all sizes of a given delimiter reside in a given font, the extra encoding point for the smallest delimiter must be supplied by defining

```
\sd@GXX
```

where G is the mathgroup and XX is the hexadecimal glyph position. `\DeclareFlexDelimiter` does that for us.

```

674 \DeclareFlexDelimiter{\rangle}{DeR}{del}{0B}{OMS}{69}
675 \DeclareFlexDelimiter{\langle}{DeL}{del}{0A}{OMS}{68}
676 \DeclareFlexDelimiter{\rbrace}{DeR}{del}{09}{OMS}{67}
677 \DeclareFlexDelimiter{\lbrace}{DeL}{del}{08}{OMS}{66}
678 \DeclareFlexDelimiter{\rceil}{DeR}{del}{07}{OMS}{65}
679 \DeclareFlexDelimiter{\lceil}{DeL}{del}{06}{OMS}{64}
680 \DeclareFlexDelimiter{\rfloor}{DeR}{del}{05}{OMS}{63}
681 \DeclareFlexDelimiter{\lfloor}{DeL}{del}{04}{OMS}{62}
682 \DeclareFlexDelimiter{\{}{DeL}{del}{00}{OT1}{28}
683 \DeclareFlexDelimiter{\}}{DeR}{del}{01}{OT1}{29}
684 \DeclareFlexDelimiter{\[]}{DeL}{del}{02}{OT1}{5B}
685 \DeclareFlexDelimiter{\]}{DeR}{del}{03}{OT1}{5D}
686 \DeclareFlexDelimiter{\lVert}{DeL}{del}{0D}{OMS}{6B}
687 \DeclareFlexDelimiter{\rVert}{DeR}{del}{0D}{OMS}{6B}
688 \DeclareFlexDelimiter{\lvert}{DeL}{del}{0C}{OMS}{6A}
689 \DeclareFlexDelimiter{\rvert}{DeR}{del}{0C}{OMS}{6A}
690 \DeclareFlexDelimiter{\Vert}{DeB}{del}{0D}{OMS}{6B}
691 \DeclareFlexDelimiter{\vert}{DeB}{del}{0C}{OMS}{6A}

```

Maybe make the vert bars mathord instead of delimiter, to discourage poor usage.

```
692 \DeclareFlexDelimiter{|}{DeB}{del}{OC}{OMS}{6A}
693 \DeclareFlexDelimiter{/}{DeB}{del}{OE}{OML}{3D}
```

These wacky delimiters need to be supported I guess for compatibility reasons.  
The DeA delimiter type is a special case used only for these arrows.

```
694 \DeclareFlexDelimiter{\lmoustache}{DeL}{del}{40}{del}{7A}
695 \DeclareFlexDelimiter{\rmoustache}{DeR}{del}{41}{del}{7B}
696 \DeclareFlexDelimiter{\lgroup}{DeL}{del}{3A}{del}{3A}
697 \DeclareFlexDelimiter{\rgroup}{DeR}{del}{3B}{del}{3B}
698 \DeclareFlexDelimiter{\bracevert}{DeB}{del}{3E}{del}{3E}
699 \DeclareFlexDelimiter{\arrowvert}{DeB}{del}{3C}{OMS}{6A}
700 \DeclareFlexDelimiter{\Arrowvert}{DeB}{del}{3D}{OMS}{6B}
701 \DeclareFlexDelimiter{\uparrow}{DeA}{del}{78}{OMS}{22}
702 \DeclareFlexDelimiter{\downarrow}{DeA}{del}{79}{OMS}{23}
703 \DeclareFlexDelimiter{\updownarrow}{DeA}{del}{3F}{OMS}{6C}
704 \DeclareFlexDelimiter{\Uparrow}{DeA}{del}{7E}{OMS}{2A}
705 \DeclareFlexDelimiter{\Downarrow}{DeA}{del}{7F}{OMS}{2B}
706 \DeclareFlexDelimiter{\Updownarrow}{DeA}{del}{77}{OMS}{6D}
707 \DeclareFlexDelimiter{\backslash}{DeB}{del}{0F}{OMS}{6E}
```

### 3 Some compound symbols

The following symbols are not robust in standard L<sup>A</sup>T<sub>E</sub>X because they use # or \mathpalette (which is not robust and contains a # in its expansion): \angle, \cong, \notin, \rightleftharpoons.

In this definition of \hbar, the symbol is cobbled together from a math italic h and the cmr overbar accent glyph.

```
708 \DeclareFlexSymbol{\hbarOrd}{Ord}{OT1}{16}
709 \DeclareFlexCompoundSymbol{\hbar}{Ord}{\hbarOrd\mkern-9mu h}
```

For \surd, the interior symbol gets math class 1 (cumulative operator) to make the glyph vertically centered on the math axis, but the desired horizontal spacing is the spacing for a mathord. (Couldn't it just be class mathopen, though?)

```
710 \DeclareFlexSymbol{\surdOrd}{Ord}{OMS}{70}
711 \DeclareFlexCompoundSymbol{\surd}{Ord}{\mathop{\surdOrd}}
```

As shown in this definition of \angle, rule dimens are not allowed to use mathunits, unfortunately.

```
712 \DeclareFlexCompoundSymbol{\angle}{Ord}{%
713   \vbox{\ialign{%
714     $ \mathrel{\scriptstyle##} \cr
715     \notRel \mathrel{\mkern14mu} \cr
716     \noalign{\nointerlineskip}%
717     \mkern2.5mu \leaders\hrule \height.34pt \hfill \mkern2.5mu \cr
718   }%
719 }
```

The `\not` function, which is defined in the `flexisym` package, requires a suitably defined `\notRel` symbol.

```
720 \DeclareFlexCompoundSymbol{\neq}{\Rel}{\not{=}}
```

```
721 \DeclareFlexCompoundSymbol{\mapsto}{\Rel}{\mapstoOrd\rightarrow}
```

The `\@vereq` function ends by centering the whole construction on the math axis, unlike `\buildrel` where the base symbol remains at its normal altitude. Furthermore, `\@vereq` leaves the math style of the top symbol as given instead of downsizing to scriptstyle.

```
722 \DeclareFlexCompoundSymbol{\cong}{\Rel}{\mathpalette\@vereq\sim}
```

The `\m@th` in the `fontmath.ltx` definition of `\notin` is superfluous unless `\c@ncel` doesn't include it (which was perhaps true in an older version of `plain.tex`?).

```
723 \providecommand*\joinord{}%
```

```
724 {cmbase | mathptmx} \renewcommand*\joinord{\mkern-3mu }
```

```
725 {mathpazo} \renewcommand*\joinord{\mkern-3.45mu }
```

```
726 \DeclareFlexCompoundSymbol{\notin}{\Rel}{\mathpalette\c@ncel\in}
```

```
727 \DeclareFlexCompoundSymbol{\rightleftharpoons}{\Rel}{\mathpalette\rlh@{}}
```

```
728 \DeclareFlexCompoundSymbol{\doteq}{\Rel}{\mathrel{\textstyle.\over=}}
```

```
729 \DeclareFlexCompoundSymbol{\hookrightarrow}{\Rel}{\lhook\relax\joinord\rightarrow}
```

```
730 \DeclareFlexCompoundSymbol{\hookleftarrow}{\Rel}{\leftarrow\joinord\rhook\relax}
```

```
731 \DeclareFlexCompoundSymbol{\bowtie}{\Rel}{\triangleleft\joinord\triangleleft}
```

```
732 \DeclareFlexCompoundSymbol{\models}{\Rel}{\mathrel{\mathop{\vert}\limits^{\mathop{\wedge}\limits}\!\!\!}\joinord=}
```

```
733 \DeclareFlexCompoundSymbol{\Longrightarrow}{\Rel}{\relbar\joinord\rightarrow}
```

```
734 \DeclareFlexCompoundSymbol{\longrightarrow}{\Rel}{\relbar\joinord\rightarrow}
```

```
735 \DeclareFlexCompoundSymbol{\Longleftarrow}{\Rel}{\leftarrow\joinord\relbar}
```

```
736 \DeclareFlexCompoundSymbol{\longleftarrow}{\Rel}{\leftarrow\joinord\relbar}
```

```
737 \DeclareFlexCompoundSymbol{\longmapsto}{\Rel}{\mathrel{\mathop{\mapstochar}\limits^{\mathop{\longmapsto}\limits}}}
```

```
738 \DeclareFlexCompoundSymbol{\longleftrightarrow}{\Rel}{\leftarrow\joinord\rightarrow}
```

```
739 \DeclareFlexCompoundSymbol{\Longleftrightarrow}{\Rel}{\leftarrow\joinord\rightarrow}
```

Here is what you get from the old definition of `\iff`.

```
\glue 2.77771 plus 2.77771
\glue(\thickmuskip) 2.77771 plus 2.77771
\OMS/cmsy/m/n/10 (
\hbox(0.0+0.0)x-1.66663
.\kern -1.66663
\OMS/cmsy/m/n/10 )
\penalty 500
\glue 2.77771 plus 2.77771
\glue(\thickmuskip) 2.77771 plus 2.77771
```

Looks like it could be simplified slightly. But it's not so easy as it looks to do it without screwing up the line breaking possibilities.

```
740 \renewcommand*\iff{%
```

```
741   \mskip\thickmuskip\Longleftrightarrow\mskip\thickmuskip
```

```
742 }
```

Some dotly symbols.

```
743 \DeclareFlexCompoundSymbol{\cdots}{Inn}{\cdotp\cdotp\cdotp}%
744 \DeclareFlexCompoundSymbol{\vdots}{Ord}{%
745   \vbox{\baselineskip4\p@\lineskiplimit\z@
746   \kern6\p@\hbox{.}\hbox{.}\hbox{.}}}
747 \DeclareFlexCompoundSymbol{\ddots}{Inn}{%
748   \mkern1mu\raise7\p@
749   \vbox{\kern7\p@\hbox{.}}\mkern2mu%
750   \raise4\p@\hbox{.}\mkern2mu\raise\p@\hbox{.}\mkern1mu%
751 }

.
752 \def\relbar{\begingroup \def\smash@{tb}%
  in case amsmath is loaded
753   \mathpalette\mathsm@sh{\mathchar"200 }\endgroup}
```

For `\Relbar` we take an equal sign of class 0 (Ord) from the operator family. For `cmr` and `mathptmx` we know this is family 0.

```
754 <cmbase | mathptmx> \def\Relbar{\mathchar"3D }
```

For the `mathpazo` setup we need to use the equal sign from `cmr` and so must insert class 0 and use the symbol from the upright symbols.

```
755 <mathpazo> \edef\Relbar{\mathchar"string"\hexnumber@\symupright3D }
```

Done.

```
756 \ExplSyntaxOff
757 </cmbase | mathpazo | mathptmx>
```

Various synonyms such as `\le` for `\leq` and `\to` for `\rightarrow` are defined in `flexisym` with `\def` instead of `\let`, for slower execution speed but smaller chance of synchronization problems.

```
758 <*msabm>
759 \ProvidesSymbols{msabm}[2001/09/08 v0.91]
760 \ExplSyntaxOn

761 \RequirePackage{amsfonts}\relax

762 \cs_gset:cpx{mg@MSA}{\hexnumber@\symAMSA}%
763 \cs_gset:cpx{mg@MSB}{\hexnumber@\symAMSB}%

764 \DeclareFlexSymbol{\boxdot}          {Bin}{MSA}{00}
765 \DeclareFlexSymbol{\boxplus}          {Bin}{MSA}{01}
766 \DeclareFlexSymbol{\boxtimes}          {Bin}{MSA}{02}
767 \DeclareFlexSymbol{\square}           {Ord}{MSA}{03}
768 \DeclareFlexSymbol{\blacksquare}      {Ord}{MSA}{04}
769 \DeclareFlexSymbol{\centerdot}         {Bin}{MSA}{05}
770 \DeclareFlexSymbol{\lozenge}          {Ord}{MSA}{06}
771 \DeclareFlexSymbol{\blacklozenge}     {Ord}{MSA}{07}
772 \DeclareFlexSymbol{\circlearrowright}  {Rel}{MSA}{08}
773 \DeclareFlexSymbol{\circlearrowleft}  {Rel}{MSA}{09}
```

In `amsfonts.sty`:

```
774 %%\DeclareFlexSymbol{\rightleftharpoons}{Rel}{MSA}{0A}
775 \DeclareFlexSymbol{\leftrightharpoons} {Rel}{MSA}{0B}
```

```

776 \DeclareFlexSymbol{\boxminus} {Bin}{MSA}{OC}
777 \DeclareFlexSymbol{\Vdash} {Rel}{MSA}{OD}
778 \DeclareFlexSymbol{\Vvdash} {Rel}{MSA}{OE}
779 \DeclareFlexSymbol{\vDash} {Rel}{MSA}{OF}
780 \DeclareFlexSymbol{\twoheadrightarrow} {Rel}{MSA}{10}
781 \DeclareFlexSymbol{\twoheadleftarrow} {Rel}{MSA}{11}
782 \DeclareFlexSymbol{\leftleftarrows} {Rel}{MSA}{12}
783 \DeclareFlexSymbol{\rightrightarrows} {Rel}{MSA}{13}
784 \DeclareFlexSymbol{\upuparrows} {Rel}{MSA}{14}
785 \DeclareFlexSymbol{\downdownarrows} {Rel}{MSA}{15}
786 \DeclareFlexSymbol{\upharpoonright} {Rel}{MSA}{16}
787 \let\restriction\upharpoonright
788 \DeclareFlexSymbol{\downharpoonright} {Rel}{MSA}{17}
789 \DeclareFlexSymbol{\upharpoonleft} {Rel}{MSA}{18}
790 \DeclareFlexSymbol{\downharpoonleft} {Rel}{MSA}{19}
791 \DeclareFlexSymbol{\rightarrowtail} {Rel}{MSA}{1A}
792 \DeclareFlexSymbol{\leftarrowtail} {Rel}{MSA}{1B}
793 \DeclareFlexSymbol{\leftrightsquigarrow} {Rel}{MSA}{1C}
794 \DeclareFlexSymbol{\rightleftarrows} {Rel}{MSA}{1D}
795 \DeclareFlexSymbol{\Lsh} {Rel}{MSA}{1E}
796 \DeclareFlexSymbol{\Rsh} {Rel}{MSA}{1F}
797 \DeclareFlexSymbol{\rightsquigarrow} {Rel}{MSA}{20}
798 \DeclareFlexSymbol{\leftrightsquigarrow} {Rel}{MSA}{21}
799 \DeclareFlexSymbol{\looparrowleft} {Rel}{MSA}{22}
800 \DeclareFlexSymbol{\looparrowright} {Rel}{MSA}{23}
801 \DeclareFlexSymbol{\circeq} {Rel}{MSA}{24}
802 \DeclareFlexSymbol{\succsim} {Rel}{MSA}{25}
803 \DeclareFlexSymbol{\gtrsim} {Rel}{MSA}{26}
804 \DeclareFlexSymbol{\gtrapprox} {Rel}{MSA}{27}
805 \DeclareFlexSymbol{\multimap} {Rel}{MSA}{28}
806 \DeclareFlexSymbol{\therefore} {Rel}{MSA}{29}
807 \DeclareFlexSymbol{\because} {Rel}{MSA}{2A}
808 \DeclareFlexSymbol{\doteqdot} {Rel}{MSA}{2B}
809 \let\doteq\dot{eqdot}
810 \DeclareFlexSymbol{\triangleq} {Rel}{MSA}{2C}
811 \DeclareFlexSymbol{\precsim} {Rel}{MSA}{2D}
812 \DeclareFlexSymbol{\lesssim} {Rel}{MSA}{2E}
813 \DeclareFlexSymbol{\lessapprox} {Rel}{MSA}{2F}
814 \DeclareFlexSymbol{\eqslantless} {Rel}{MSA}{30}
815 \DeclareFlexSymbol{\eqslantgtr} {Rel}{MSA}{31}
816 \DeclareFlexSymbol{\curlyeqprec} {Rel}{MSA}{32}
817 \DeclareFlexSymbol{\curlyeqsucc} {Rel}{MSA}{33}
818 \DeclareFlexSymbol{\preccurlyeq} {Rel}{MSA}{34}
819 \DeclareFlexSymbol{\leqq} {Rel}{MSA}{35}
820 \DeclareFlexSymbol{\leqslant} {Rel}{MSA}{36}
821 \DeclareFlexSymbol{\lessgtr} {Rel}{MSA}{37}
822 \DeclareFlexSymbol{\backprime} {Ord}{MSA}{38}
823 \DeclareFlexSymbol{\risingdotseq} {Rel}{MSA}{3A}
824 \DeclareFlexSymbol{\fallingdotseq} {Rel}{MSA}{3B}
825 \DeclareFlexSymbol{\succcurlyeq} {Rel}{MSA}{3C}

```

```

826 \DeclareFlexSymbol{\geqq} {Rel}{MSA}{3D}
827 \DeclareFlexSymbol{\geqslant} {Rel}{MSA}{3E}
828 \DeclareFlexSymbol{\gtrless} {Rel}{MSA}{3F}

in amsfonts.sty

829 %% \DeclareFlexSymbol{\sqsubset} {Rel}{MSA}{40}
830 %% \DeclareFlexSymbol{\sqsupset} {Rel}{MSA}{41}
831 \DeclareFlexSymbol{\vartriangleright} {Rel}{MSA}{42}
832 \DeclareFlexSymbol{\vartriangleleft} {Rel}{MSA}{43}
833 \DeclareFlexSymbol{\trianglerighteq} {Rel}{MSA}{44}
834 \DeclareFlexSymbol{\trianglelefteq} {Rel}{MSA}{45}
835 \DeclareFlexSymbol{\bigstar} {Ord}{MSA}{46}
836 \DeclareFlexSymbol{\between} {Rel}{MSA}{47}
837 \DeclareFlexSymbol{\blacktriangledown} {Ord}{MSA}{48}
838 \DeclareFlexSymbol{\blacktriangleright} {Rel}{MSA}{49}
839 \DeclareFlexSymbol{\blacktriangleleft} {Rel}{MSA}{4A}
840 \DeclareFlexSymbol{\vartriangle} {Rel}{MSA}{4D}
841 \DeclareFlexSymbol{\blacktriangle} {Ord}{MSA}{4E}
842 \DeclareFlexSymbol{\triangledown} {Ord}{MSA}{4F}
843 \DeclareFlexSymbol{\eqcirc} {Rel}{MSA}{50}
844 \DeclareFlexSymbol{\lesseqgtr} {Rel}{MSA}{51}
845 \DeclareFlexSymbol{\gtreqless} {Rel}{MSA}{52}
846 \DeclareFlexSymbol{\lesseqqgtr} {Rel}{MSA}{53}
847 \DeclareFlexSymbol{\gtreqqless} {Rel}{MSA}{54}
848 \DeclareFlexSymbol{\rightarrowarrow} {Rel}{MSA}{56}
849 \DeclareFlexSymbol{\leftarrowarrow} {Rel}{MSA}{57}
850 \DeclareFlexSymbol{\veebar} {Bin}{MSA}{59}
851 \DeclareFlexSymbol{\barwedge} {Bin}{MSA}{5A}
852 \DeclareFlexSymbol{\doublebarwedge} {Bin}{MSA}{5B}

In amsfonts.sty

853 %\DeclareFlexSymbol{\angle} {Ord}{MSA}{5C}
854 \DeclareFlexSymbol{\measuredangle} {Ord}{MSA}{5D}
855 \DeclareFlexSymbol{\sphericalangle} {Ord}{MSA}{5E}
856 \DeclareFlexSymbol{\varproto} {Rel}{MSA}{5F}
857 \DeclareFlexSymbol{\smallsmile} {Rel}{MSA}{60}
858 \DeclareFlexSymbol{\smallfrown} {Rel}{MSA}{61}
859 \DeclareFlexSymbol{\Subset} {Rel}{MSA}{62}
860 \DeclareFlexSymbol{\Supset} {Rel}{MSA}{63}
861 \DeclareFlexSymbol{\Cup} {Bin}{MSA}{64}
862 \let\doublecup\Cup
863 \DeclareFlexSymbol{\Cap} {Bin}{MSA}{65}
864 \let\doublecap\Cap
865 \DeclareFlexSymbol{\curlywedge} {Bin}{MSA}{66}
866 \DeclareFlexSymbol{\curlyvee} {Bin}{MSA}{67}
867 \DeclareFlexSymbol{\leftthreetimes} {Bin}{MSA}{68}
868 \DeclareFlexSymbol{\rightthreetimes} {Bin}{MSA}{69}
869 \DeclareFlexSymbol{\subsetneqq} {Rel}{MSA}{6A}
870 \DeclareFlexSymbol{\supsetneqq} {Rel}{MSA}{6B}
871 \DeclareFlexSymbol{\bumpeq} {Rel}{MSA}{6C}
872 \DeclareFlexSymbol{\Bumpeq} {Rel}{MSA}{6D}

```

```

873 \DeclareFlexSymbol{\lll}{\let\llless\lll} {Rel}{MSA}{6E}
874 \let\llless\lll
875 \DeclareFlexSymbol{\ggg}{\let\gggr\ggg} {Rel}{MSA}{6F}
876 \let\gggr\ggg
877 \DeclareFlexSymbol{\circledS}{\circledS} {Ord}{MSA}{73}
878 \DeclareFlexSymbol{\pitchfork}{\pitchfork} {Rel}{MSA}{74}
879 \DeclareFlexSymbol{\dotplus}{\dotplus} {Bin}{MSA}{75}
880 \DeclareFlexSymbol{\backsim}{\backsim} {Rel}{MSA}{76}
881 \DeclareFlexSymbol{\backsimeq}{\backsimeq} {Rel}{MSA}{77}
882 \DeclareFlexSymbol{\complement}{\complement} {Ord}{MSA}{7B}
883 \DeclareFlexSymbol{\intercal}{\intercal} {Bin}{MSA}{7C}
884 \DeclareFlexSymbol{\circledcirc}{\circledcirc} {Bin}{MSA}{7D}
885 \DeclareFlexSymbol{\circledast}{\circledast} {Bin}{MSA}{7E}
886 \DeclareFlexSymbol{\circleddash}{\circleddash} {Bin}{MSA}{7F}

Begin AMSb declarations

887 \DeclareFlexSymbol{\lvertneqq}{\lvertneqq} {Rel}{MSB}{00}
888 \DeclareFlexSymbol{\gvertneqq}{\gvertneqq} {Rel}{MSB}{01}
889 \DeclareFlexSymbol{\nleq}{\nleq} {Rel}{MSB}{02}
890 \DeclareFlexSymbol{\ngeq}{\ngeq} {Rel}{MSB}{03}
891 \DeclareFlexSymbol{\nless}{\nless} {Rel}{MSB}{04}
892 \DeclareFlexSymbol{\ngtr}{\ngtr} {Rel}{MSB}{05}
893 \DeclareFlexSymbol{\nprec}{\nprec} {Rel}{MSB}{06}
894 \DeclareFlexSymbol{\nsucc}{\nsucc} {Rel}{MSB}{07}
895 \DeclareFlexSymbol{\lneqq}{\lneqq} {Rel}{MSB}{08}
896 \DeclareFlexSymbol{\gneqq}{\gneqq} {Rel}{MSB}{09}
897 \DeclareFlexSymbol{\nleqslant}{\nleqslant} {Rel}{MSB}{0A}
898 \DeclareFlexSymbol{\ngeqslant}{\ngeqslant} {Rel}{MSB}{0B}
899 \DeclareFlexSymbol{\lneq}{\lneq} {Rel}{MSB}{0C}
900 \DeclareFlexSymbol{\gneq}{\gneq} {Rel}{MSB}{0D}
901 \DeclareFlexSymbol{\npreceq}{\npreceq} {Rel}{MSB}{0E}
902 \DeclareFlexSymbol{\nsucceq}{\nsucceq} {Rel}{MSB}{0F}
903 \DeclareFlexSymbol{\precnsim}{\precnsim} {Rel}{MSB}{10}
904 \DeclareFlexSymbol{\succnsim}{\succnsim} {Rel}{MSB}{11}
905 \DeclareFlexSymbol{\lnsim}{\lnsim} {Rel}{MSB}{12}
906 \DeclareFlexSymbol{\gnsim}{\gnsim} {Rel}{MSB}{13}
907 \DeclareFlexSymbol{\nleqq}{\nleqq} {Rel}{MSB}{14}
908 \DeclareFlexSymbol{\ngeqq}{\ngeqq} {Rel}{MSB}{15}
909 \DeclareFlexSymbol{\precneqq}{\precneqq} {Rel}{MSB}{16}
910 \DeclareFlexSymbol{\succcneqq}{\succcneqq} {Rel}{MSB}{17}
911 \DeclareFlexSymbol{\precnapprox}{\precnapprox} {Rel}{MSB}{18}
912 \DeclareFlexSymbol{\succnapprox}{\succnapprox} {Rel}{MSB}{19}
913 \DeclareFlexSymbol{\lnapprox}{\lnapprox} {Rel}{MSB}{1A}
914 \DeclareFlexSymbol{\gnapprox}{\gnapprox} {Rel}{MSB}{1B}
915 \DeclareFlexSymbol{\nsim}{\nsim} {Rel}{MSB}{1C}
916 \DeclareFlexSymbol{\ncong}{\ncong} {Rel}{MSB}{1D}
917 \DeclareFlexSymbol{\diagup}{\diagup} {Ord}{MSB}{1E}
918 \DeclareFlexSymbol{\diagdown}{\diagdown} {Ord}{MSB}{1F}
919 \DeclareFlexSymbol{\varsubsetneq}{\varsubsetneq} {Rel}{MSB}{20}
920 \DeclareFlexSymbol{\varsupsetneq}{\varsupsetneq} {Rel}{MSB}{21}

```

```

921 \DeclareFlexSymbol{\nsubseteqqq} {Rel}{MSB}{22}
922 \DeclareFlexSymbol{\nsupseteqqq} {Rel}{MSB}{23}
923 \DeclareFlexSymbol{\subsetneqq} {Rel}{MSB}{24}
924 \DeclareFlexSymbol{\supsetneqq} {Rel}{MSB}{25}
925 \DeclareFlexSymbol{\varsubsetneqq} {Rel}{MSB}{26}
926 \DeclareFlexSymbol{\varsupsetneqq} {Rel}{MSB}{27}
927 \DeclareFlexSymbol{\subsetneq} {Rel}{MSB}{28}
928 \DeclareFlexSymbol{\supsetneq} {Rel}{MSB}{29}
929 \DeclareFlexSymbol{\nsubseteq} {Rel}{MSB}{2A}
930 \DeclareFlexSymbol{\nsupseteq} {Rel}{MSB}{2B}
931 \DeclareFlexSymbol{\nparallel} {Rel}{MSB}{2C}
932 \DeclareFlexSymbol{\nmid} {Rel}{MSB}{2D}
933 \DeclareFlexSymbol{\nshortmid} {Rel}{MSB}{2E}
934 \DeclareFlexSymbol{\nshortparallel} {Rel}{MSB}{2F}
935 \DeclareFlexSymbol{\nvdash} {Rel}{MSB}{30}
936 \DeclareFlexSymbol{\nVdash} {Rel}{MSB}{31}
937 \DeclareFlexSymbol{\nvDash} {Rel}{MSB}{32}
938 \DeclareFlexSymbol{\nVDash} {Rel}{MSB}{33}
939 \DeclareFlexSymbol{\ntrianglelefteq} {Rel}{MSB}{34}
940 \DeclareFlexSymbol{\ntrianglelefteq} {Rel}{MSB}{35}
941 \DeclareFlexSymbol{\ntriangleleft} {Rel}{MSB}{36}
942 \DeclareFlexSymbol{\ntriangleright} {Rel}{MSB}{37}
943 \DeclareFlexSymbol{\nleftarrow} {Rel}{MSB}{38}
944 \DeclareFlexSymbol{\nrightarrow} {Rel}{MSB}{39}
945 \DeclareFlexSymbol{\nLeftarrow} {Rel}{MSB}{3A}
946 \DeclareFlexSymbol{\nRightarrow} {Rel}{MSB}{3B}
947 \DeclareFlexSymbol{\nLeftrightarrow} {Rel}{MSB}{3C}
948 \DeclareFlexSymbol{\nleftrightarrow} {Rel}{MSB}{3D}
949 \DeclareFlexSymbol{\divideontimes} {Bin}{MSB}{3E}
950 \DeclareFlexSymbol{\varnothing} {Ord}{MSB}{3F}
951 \DeclareFlexSymbol{\nexists} {Ord}{MSB}{40}
952 \DeclareFlexSymbol{\Finv} {Ord}{MSB}{60}
953 \DeclareFlexSymbol{\Game} {Ord}{MSB}{61}

```

In amsfonts.sty:

```

954 %%\DeclareFlexSymbol{\mho} {Ord}{MSB}{66}
955 \DeclareFlexSymbol{\eth} {Ord}{MSB}{67}
956 \DeclareFlexSymbol{\eqsim} {Rel}{MSB}{68}
957 \DeclareFlexSymbol{\beth} {Ord}{MSB}{69}
958 \DeclareFlexSymbol{\gimel} {Ord}{MSB}{6A}
959 \DeclareFlexSymbol{\daleth} {Ord}{MSB}{6B}
960 \DeclareFlexSymbol{\lessdot} {Bin}{MSB}{6C}
961 \DeclareFlexSymbol{\gtrdot} {Bin}{MSB}{6D}
962 \DeclareFlexSymbol{\ltimes} {Bin}{MSB}{6E}
963 \DeclareFlexSymbol{\rtimes} {Bin}{MSB}{6F}
964 \DeclareFlexSymbol{\shortmid} {Rel}{MSB}{70}
965 \DeclareFlexSymbol{\shortparallel} {Rel}{MSB}{71}
966 \DeclareFlexSymbol{\smallsetminus} {Bin}{MSB}{72}
967 \DeclareFlexSymbol{\thicksim} {Rel}{MSB}{73}
968 \DeclareFlexSymbol{\thickapprox} {Rel}{MSB}{74}

```

```

969 \DeclareFlexSymbol{\approxeq}      {Rel}{MSB}{75}
970 \DeclareFlexSymbol{\succapprox}     {Rel}{MSB}{76}
971 \DeclareFlexSymbol{\precapprox}     {Rel}{MSB}{77}
972 \DeclareFlexSymbol{\curvearrowleft}   {Rel}{MSB}{78}
973 \DeclareFlexSymbol{\curvearrowright}  {Rel}{MSB}{79}
974 \DeclareFlexSymbol{\digamma}        {Ord}{MSB}{7A}
975 \DeclareFlexSymbol{\varkappa}       {Ord}{MSB}{7B}
976 \DeclareFlexSymbol{\Bbbk}           {Ord}{MSB}{7C}
977 \DeclareFlexSymbol{\hslash}          {Ord}{MSB}{7D}

In amsfonts.sty:
978 %%\DeclareFlexSymbol{\hbar}          {Ord}{MSB}{7E}
979 \DeclareFlexSymbol{\backepsilon}     {Rel}{MSB}{7F}
980 \ExplSyntaxOff
981 
```

## Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\"	7, 12	\@symDeB .....
\'	373	\@symDeL .....
\*	374	\@symDeR .....
\-	363, 376, 378, 380, 383	\@symErr .....
\.	349, 375	\@symOrd .....
\vee	384	\@symPun .....
\colon	385	\@symRel .....
\=	364	\@symVar .....
\@begindocumenthook	366, 368	\@symextension .....
\@firstofone	100	\@symtype . 83–93, 96–98, 100, 265, 344
\@gobble	13, 346	\@symtype@ord .....
\@gobblethree	328	\@tempb ..... 228, 233, 237, 334, 335
\@height	717	\@typeset@protect .....
\@ifpackageloaded	361	\@vereq .....
\@ifpackagewith	423, 428	\_ ..... 35, 38, 41, 44, 349
\@ifundefined	284, 290	\  .....
\@nil	347, 350	<b>A</b>
\@onefilewithoptions	335	\active .....
\@sym	13, 15, 94, 229, 255, 264, 329, 344	\aleph .....
\@sym@ord	344, 347	\alpha .....
\@sym@ord@a	347, 350	\amalg .....
\@symAcc	94	\angle .....
\@symBin	85	\approx .....
\@symCOi	88	\approxeq .....
\@symCOs	89	\Arrowvert .....
\@symDeA	93	\arrowvert .....

\ast	569, 617	\bracevert	698
\asymp	655	\buildrel	728
\AtBeginDocument	371	\bullet	603
\AtEndOfPackage	6	\Bumpeq	872
		\bumpeq	871

## B

\backepsilon	979
\backprime	822
\backsim	880
\backsimeq	881
\backslash	707
\barwedge	851
\baselineskip	745
\Bbbk	976
\because	807
\begingroup	807 227, 254, 261, 342, 348, 362, 752
\beta	468
\beth	957
\between	836
\bigcap	664
\bigcirc	614
\bigcup	665
\bigodot	671
\bigoplus	670
\bigotimes	669
\bigoslash	673
\bigstar	835
\bigtriangledown	591
\bigtriangleup	590
\biguplus	663
\bigvee	661
\bigwedge	662
\binrel@	326
\binrel@@	305, 318–324
\binrel@a	317, 329
\binrel@sym	304, 329
\blacklozenge	771
\blacksquare	768
\blacktriangle	841
\blacktriangledown	837
\blacktriangleleft	839
\blacktriangleright	838
\bot	580
\bowtie	731
\box	293, 298, 301
\boxdot	764
\boxminus	776
\boxplus	765
\boxtimes	766

## C

\c@ncel	726
\Cap	863, 864
\cap	594
\catcode	7, 12, 224, 225, 259, 260
\cdot	616
\cdotp	658, 659
\cdotp\cdotp	659, 743
\cdots	743
\centerdot	769
\char	257
\check@mathfonts	262
\chi	487
\circ	613
\circceq	801
\circlearrowleft	773
\circlearrowright	772
\circledast	885
\circledcirc	884
\circleddash	886
\circledS	877
\cleaders	292, 296, 300
\clist	334
\clubsuit	585
\colon	437
\complement	882
\cong	722
\coprod	660
\copy	292, 297
\crcr	714, 715, 717
\cs	34, 37, 40, 43, 50–62, 64, 67, 68, 71, 74, 78, 79, 83– 94, 96–98, 102–114, 116–143, 145–160, 162–189, 192, 194– 221, 228, 242, 244, 255, 263– 267, 270, 358, 412–422, 424, 426, 429, 431–433, 659, 762, 763
\csname	248
\Cup	861, 862
\cup	595
\curlyeqprec	816
\curlyeqsucc	817
\curlyvee	866
\curlywedge	865

\curvearrowleft	972	<b>E</b>
\curvearrowright	973	\edef ..... 5, 224, 259, 755 \ell ..... 498 \else 16, 234, 273, 307–313, 354, 377, 379 \emptyset ..... 577 \endcsname ..... 248 \endgroup ..... ..... 239, 257, 277, 342, 349, 369, 753
<b>D</b>		\endinput ..... 406 \epsilon ..... 471 \eqcirc ..... 843 \eqsim ..... 956 \eqslantgr ..... 815 \eqslantless ..... 814 \equiv ..... 654 \eta ..... 473 \eth ..... 955 \everymath ..... 268 \ExecuteOptions ..... 393 \exists ..... 583
\dagger	597	\exp 16, 65, 69, 75, 76, 229, 230, 232, ..... 244, 248, 313, 314, 335, 347, 418
\daleth	959	\expandafter ..... 274, 368
\dashv	624	\ExplSyntaxOff ..... 756, 980
\ddagger	596	\ExplSyntaxOn ..... 411, 760
\ddots	747	
\DeclareFlexCompoundSymbol	..... ..... 247, 709, 711, 712, 720–722, 726–739, 743, 744, 747	
\DeclareFlexDelimiter	242, 674–707	
\DeclareFlexSymbol	. 226, 243, 434– 565, 567–658, 660–673, 708, 710, 764–786, 788–808, 810– 861, 863, 865–873, 875, 877–979	
\DeclareOption	14, 388, 390–392	
\DeclareRobustCommand	..... ..... 248, 251, 252, 281, 340, 341	
\def	15, 19–33, 226, 247, 253, 261, 269, 285, 291, 295, 299, 304, 317–324, 326, 332, 344, 346, 347, 350, 363, 372, 566, 752, 754	
\Delta	442	
\delta	470	
\diagdown	918	
\diagup	917	
\diamond	602	
\diamondsuit	586	
\digamma	974	
\displaylimits	47, 49	
\div	605	
\divideontimes	949	
\do	5, 11	
\Doteq	809	
\doteq	728	
\doteqdot	808, 809	
\dotplus	879	
\doublebarwedge	852	
\doublecap	864	
\doublecup	862	
\Downarrow	705	
\downarrow	702	
\downdownarrows	785	
\downharpoonleft	790	
\downharpoonright	788	
\dp	287	
		<b>F</b>
		\fallingdotseq ..... 824
		\fi 16, 238, 276, 313, 356, 381, 382
		\Finv ..... 952
		\flat ..... 501
		\flexi@stop ..... 364, 368
		\forall ..... 582
		\frown ..... 508
		<b>G</b>
		\Game ..... 953
		\Gamma ..... 441
		\gamma ..... 469
		\gdef ..... 318–324
		\ge ..... 399
		\geq ..... 399, 634
		\geqq ..... 826
		\geqslant ..... 827
		\gets ..... 402
		\gg ..... 646
		\ggg ..... 875, 876
		\gggr ..... 876
		\gimel ..... 958
		\global ..... 101

\gnapprox	914	\kern	746, 749
\gneq	900		
\gneqq	896		
\gnsim	906	L	
\gtrapprox	804	\Lambda	444
\gtrdot	961	\lambda	477
\gtreqless	845	\land	396
\gtreqqless	847	\langle	675
\gtrless	828	\lrcorner	677
\gtrsim	803	\lceil	236, 274, 349
\gvertneqq	888	\lceil\rfloor	679
		\lfloor	566
		\ldotp	566
		\ldotp\ldotp\ldotp	565, 566
		\le	398
H			
\hbar	709, 978	\leaders	717
\hbarOrd	708, 709	\leavevmode	281
\hbox	282, 286, 293, 297, 301, 327, 746, 749, 750	\Leftarrow	631, 735, 739
\heartsuit	587	\leftarrow	
\hexnumber@	412–415, 426, 755, 762, 763	. 296, 300, 402, 649, 730, 736, 738	
\hfill	293, 297, 301, 717	\leftarrowfill@	295
\hookleftarrow	730	\leftarrowtail	792
\hookrightarrow	729	\leftharpoondown	510
\hrule	717	\leftharpoonup	509
\hslash	977	\leftleftarrows	782
\ht	287, 291, 295, 299	\Leftrightarrow	630
		\leftarrowarrow	648
		\leftarrowarrowfill@	299
I		\leftarrowarrow	793
\ialign	713	\leftrightharpoons	775
\if	351	\lefttrightsquigarrow	798
\ifcat	232, 271	\leftthreetimes	867
\iff	740	\leq	398, 633
\ifmmode	267	\leqq	819
\ifnum	376, 378	\leqslant	820
\iftrue	267	\lessapprox	813
\ifix	16, 306–312	\lessdot	960
\Im	574	\lesseqgtr	844
\imath	496	\lesseqgtr	846
\in	644, 726	\lessgtr	821
\infty	575	\lesssim	812
\int	666	\let	11, 13, 47–49, 100, 101, 233, 237, 249, 328, 329, 344,
\intercal	883	345, 787, 809, 862, 864, 874, 876	
\intlimits	48, 56, 88	\lfloor	681
\iota	475	\lgroupt	696
J		\lhookRel	567, 729
\jmath	497	\lineskiplimit	745
\joinord	723–725, 729–736, 738, 739	\ll	647
K		\Lleftarrow	849
\kappa	476	\lll	873, 874
		\llless	874

\lmoustache	694	\mathchars@reset	342, 344
\lnapprox	913	\mathchoice	328
\lneq	899	\mathclose	91, 97
\lneqq	895	\mathcode	235, 363,
\lnot	395	364, 373–376, 378, 380, 383–385	
\lnsim	905	\mathinner	98
\long	363	\mathop	88, 89, 711
\Longleftarrow	735	\mathopen	90, 96
\longleftarrow	736	\mathord	83, 84, 92
\Longleftrightarrow	739, 741	\mathpalette	722, 726, 727, 753
\longleftrightarrow	738	\mathpunct	87, 659
\longmapsto	737	\mathrel	86, 93, 715
\Longrightarrow	733	\mathsm@sh	753
\longrightarrow	734, 737	\Mathstrutbox@	287
\looparrowleft	799	\measuredangle	854
\looparrowright	800	\mg@acc	24
\lor	397	\mg@arr	23
\lowercase	237, 275, 349	\mg@Bbb	30
\lozenge	770	\mg@bflatin	29
\Lsh	795	\mg@bin	19, 416, 431, 432
\ltimes	962	\mg@cal	31
\lVert	686	\mg@cop	25, 433
\lvert	688	\mg@del	22, 417, 433
\lvertneqq	887	\mg@digit	33, 418, 422
		\mg@frak	32
		\mg@Greek	28, 422, 424, 429
		\mg@greek	27, 421
M		\mg@Latin	420
\m@Bin	52, 53, 104, 105	\mg@latin	26, 419–421, 424, 429
\m@C0i	56, 108	\mg@nre	21
\m@C0s	55, 107	\mg@OML	419
\m@DeA	60, 112	\mg@OMS	416
\m@DeB	59, 111	\mg@OMX	417
\m@DeL	57, 109	\mg@ord	432
\m@DeR	58, 110	\mg@rel	20, 431
\m@Ord	50, 102	\mho	954
\m@Pun	54, 106	\mid	623
\m@Rad	61, 113	\mkern	269, 270, 292–
\m@th	291, 295, 299, 714	294, 296–298, 300–302, 709,	
\m@Var	51, 103	715, 717, 724, 725, 748–750	
\mapsto	721	\models	732
\mapstochar	737	\mp	611
\mapstoOrd	657, 721	\mskip	270, 741
\math	34, 37, 40, 43, 50–62, 64, 65, 67–69, 71, 74, 75, 78, 83–94, 96–98, 102–114, 116– 143, 145–160, 162–189, 192, 194–221, 223, 306–312, 318– 324, 340, 352, 353, 355, 358, 359	\mu	478
\mathbin	85	\multimap	805
\mathchar	753–755	\muskip	269
\mathchardef	363, 364, 380	N	
		\nabla	578
		\namelimits	49

\natural	502	\number	7
\ncong	916	\nVDash	938
\ne	400	\nVdash	936
\nearrow	626	\nvDash	937
\neg	395, 584	\nvdash	935
\neq	400, 720	\nwarrow	628
\newcommand	333, 339		
\newmcodes@	372		
\nexists	951	\odot	606
\next	363, 368	\oint	672
\ngeq	890	\Omega	451
\ngeqq	908	\omega	489
\ngeqslant	898	\ominus	609
\ngtr	892	\oplus	610
\ni	401, 645	\OrdSymbol	83– 93, 96–98, 266, 294, 296, 300, 302, 314, 318–324, 340, 341, 345
\nLeftarrow	945	\oslash	607
\leftarrow	943	\otimes	608
\Leftrightarrow	947	\over	728
\leftrightarrow	948	\owns	401
\leq	889		
\leqq	907		
\leqslant	897		
\nless	891		
\nmid	932	\p@	745, 746, 748–750
\noalign	716	\parallel	622
\noexpand	6, 271	\partial	500
\nointerlineskip	716	\PassOptionsToPackage	389
\nolimits	48	\perp	653
\not	340, 720	\Phi	449
\notin	726	\phi	486
\notRel	340, 656, 715	\Pi	446
\nparallel	931	\pi	481
\nprec	893	\pitchfork	878
\npreceq	901	\pm	612
\nrightarrow	946	\prec	636
\nrightarrow	944	\precapprox	971
\nshortmid	933	\preccurlyeq	818
\nshortparallel	934	\preceq	639
\nsim	915	\precnapprox	911
\nsubseteq	929	\precneqq	909
\nsubseteqq	921	\precnsim	903
\nsucc	894	\precsim	811
\nsuccseq	902	\prg	255
\nsupseteq	930	\prime	282, 576
\nsupseteqq	922	\ProcessOptions	394
\ntriangleleft	941	\prod	667
\ntrianglelefteq	940	\proto	619
\ntriangleright	942	\protect	16
\ntrianglerighteq	939	\providecommand	280, 723
\nu	479	\ProvidesExplFile	338

\ProvidesExplPackage	3	\searrow	627
\ProvidesFile	339	\setbox	286, 327
\ProvidesSymbols	339, 408–410, 759	\setboxz@h	291, 295, 299
\Psi	450	\setminus	615
\psi	488	\sharp	503
<b>R</b>			
\raise	282, 748, 750	\shortmid	964
\rangle	674	\shortparallel	965
\rbrace	676	\Sigma	447
\rceil	678	\sigma	483
\Re	573	\sim	651, 722
\relax	8, 11, 232, 235, 236, 249, 271, 274, 345, 363, 364, 380, 385, 394, 761	\simeq	652
\Relbar	733, 735, 754, 755	\smallfrown	858
\relbar	291, 295, 299, 734, 736, 752	\smallint	589
\renewcommand	395–404, 724, 725, 740	\smallsetminus	966
\RequirePackage	2, 405, 761	\smallsmile	857
\resetMathstrut@	285	\smash@	752
\restriction	787	\smile	507
\rfloor	680	\space	373–376, 378, 383–385
\rgroup	697	\spadesuit	588
\rho	482	\sphericalangle	855
\rhookRel	568, 730	\sqcap	598
\Rightarrow	632, 733, 739	\sqcup	599
\rightarrow	294, 302, 403, 650, 721, 729, 734, 738	\sqsubset	829
\rightarrowfill@	291	\sqsubseteq	620
\rightarrowtail	791	\sqsupset	830
\rightharpoondown	512	\sqsupseteq	621
\rightharpoonup	511	\square	767
\rightleftarrows	794	\star	506
\rightleftharpoons	727, 774	\std@equal	364
\rightrightarrow	783	\std@minus	363, 380
\rightsquigarrow	797	\string	274, 347, 755
\rightthreetimes	868	\Subset	859
\risingdotseq	823	\subset	641
\rlh@	727	\subsetneq	643
\rmoustache	695	\subsetneqq	869
\Rightarrow	848	\subsetneqeq	927
\Rsh	796	\subsetneqq	923
\rtimes	963	\succ	635
\rVert	687	\succapprox	970
\rvert	689	\succcurlyeq	825
<b>S</b>			
\scriptchar	252	\succceq	638
\scriptfont	252, 282	\succnapprox	912
\scriptstyle	714	\succneqq	910
		\succnsim	904
		\succsim	802
		\sum	668
		\sumlimits	47, 55, 89
\Supset		\Upset	860
\supset		\upset	640
\supseteq		\upseteq	642

\supseteqq	870	\Updownarrow	706
\supsetneq	928	\updownarrow	703
\supsetneqq	924	\upharpoonleft	789
\surd	711	\upharpoonright	786, 787
\surdOrd	710, 711	\uplus	600
\swarrow	629	\Upsilon	448
\sym@global	101, 233, 235, 237, 249	\upsilon	485
\symAMSA	762	\upuparrows	784
\symAMSb	763	\use	16, 65, 69, 75, 76, 81, 244, 265, 266, 268
\symlargesymbols	415	\usesymbols	333, 390–392
\symletters	413		
\symoperators	412		
\symsymbols	414		
\symupright	426, 755		
<b>T</b>			
\tau	484	\varepsilon	490
\tex	35, 38, 41, 44	\kappa	975
\text@char	251, 252, 261, 282	\varnothing	950
\text@char@sym	253, 264	\varphi	495
\text@script@char	256, 263	\varpi	492
\textchar	251, 286	\varpropto	856
\textfont	251	\varrho	493
\textprime	280, 281	\varsigma	494
\textstyle	728	\varsubsetneq	919
\the	224, 256, 259, 366	\varsubsetneqq	925
\therefore	806	\varsupsetneq	920
\Theta	443	\varsupsetneqq	926
\theta	474	\vartheta	491
\thickapprox	968	\vartriangle	840
\thickmuskip	741	\vartriangleleft	832
\thicksim	967	\vartriangleright	831
\times	618	\vbox	713, 745, 749
\tmp	224, 241, 259, 279	\vdash	777
\to	403	\vDash	779
\toks@	365, 366	\vdash	625
\top	579	\vdots	744
\triangle	581	\vee	397, 593
\triangledown	842	\veebar	850
\triangleleft	504, 731	\Vert	404, 690
\trianglelefteq	834	\vert	286, 691, 732
\triangleq	810	\vDash	778
\triangleright	505, 731		
\trianglerighteq	833		
\twoheadleftarrow	781		
\twoheadrightarrow	780		
<b>U</b>			
\Uparrow	704	\wedge	396, 592
\uparrow	701	\wp	499
		\wr	604
<b>X</b>			
\xdef	305, 366		
\Xi	445		
\xi	480		

<b>Z</b>	293, 295, 297–299, 301, 327, 745
<b>\z@</b> . . . . .	224, 225, 236, 259, 260, 269, 274, 286, 287, 291–
<b>\zeta</b> . . . . .	472